DATASHEET - T6-160-6/V/SVB/HI11

Main switch, T6, 160 A, rear mounting, 6 contact unit(s), 6 pole, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Part no. **T6-160-6/V/SVB/HI11**
200619

Product name	Eaton Moeller® series T6 Main switch
Part no.	T6-160-6/V/SVB/HI11
EAN	4015082006198
Product Length/Depth	200 millimetre
Product height	140 millimetre
Product width	225 millimetre
Product weight	2.2 kilogram
Certifications	IEC/EN 60947-3 IEC/EN 60947 IEC/EN 60204 VDE 0660
Product Tradename	T6
Product Type	Main switch
Product Sub Type	None
Catalog Notes	Rated Short-time Withstand Current (Icw) for a time of 1 second
Features	Version as maintenance-/service switch Version as main switch
Fitted with:	Red rotary handle and yellow locking ring
Functions	Interlockable Emergency switching off function
Locking facility	Lockable in the 0 (Off) position
Number of poles	6
Degree of protection	NEMA 12
Degree of protection (front side)	IP65
Lifespan, mechanical	100,000 Operations
Mounting method	Rear mounting
Mounting position	As required
Number of contact units	6
Operating frequency	50 Operations/h
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	8000 V AC
Safe isolation	440 V AC, Between the contacts, According to EN 61140
Safety parameter (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
Suitable for	Ground mounting Intermediate mounting
Switching angle	90 °
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Ambient operating temperature (enclosed) - min	-25 °C
Ambient operating temperature (enclosed) - max	40 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacity	1 x 70 mm^2, solid or stranded 1 x 13 x 3 mm Number of segments x width x thickness, copper strip 2 x 35 mm^2, solid or stranded 1 x 50 mm^2, flexible with ferrules to DIN 46228

	2 x 25 mm², flexible with ferrules to DIN 46228 2 x 13 x 1.5 mm Number of segments x width x thickness, copper strip
Screw size	M5, Inbus, Terminal screw
Tightening torque	39.8 lb-in, Screw terminals 4.5 Nm, Screw terminals
Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)	1280 A
Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)	900 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)	880 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)	340 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V	103 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	85 A
Rated operational current (Ie) at AC-3, 500 V	78 A
Rated operational current (Ie) at AC-3, 660 V, 690 V	42 A
Rated operational current (Ie) at AC-21, 440 V	160 A
Rated operational current (Ie) at AC-23A, 230 V	103 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V	105 A
Rated operational current (Ie) at AC-23A, 500 V	106 A
Rated operational current (Ie) at AC-23A, 690 V	42 A
Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms	125 A
Rated operational current (Ie) at DC-13, control switches L/R = 50 ms	125 A
Rated operational current (Ie) at DC-23A, 24 V	125 A
Rated operational current (Ie) at DC-23A, 48 V	125 A
Rated operational current (Ie) at DC-23A, 60 V	125 A
Rated operational current (Ie) at DC-23A, 120 V	50 A
Rated operational current (Ie) star-delta at AC-3, 220/230 V	103 A
Rated operational current (Ie) star-delta at AC-3, 380/400 V	85 A
Rated operational current (Ie) star-delta at AC-3, 500 V	78 A
Rated operational current (Ie) star-delta at AC-3, 690 V	42 A
Rated operational power at AC-3, 380/400 V, 50 Hz	45 kW
Rated operational power at AC-3, 415 V, 50 Hz	45 kW
Rated operational power at AC-3, 500 V, 50 Hz	55 kW
Rated operational power at AC-3, 690 V, 50 Hz	37 kW
Rated operational power at AC-23A, 220/230 V, 50 Hz	30 kW
Rated operational power at AC-23A, 400 V, 50 Hz	55 kW
Rated operational power at AC-23A, 500 V, 50 Hz	75 kW
Rated operational power at AC-23A, 690 V, 50 Hz	37 kW
Rated operational power star-delta at 220/230 V, 50 Hz	30 kW
Rated operational power star-delta at 380/400 V, 50 Hz	45 kW
Rated operational power star-delta at 500 V, 50 Hz	55 kW
Rated operational power star-delta at 690 V, 50 Hz	37 kW
Rated operational voltage (Ue) at AC - min	690 V
Rated operational voltage (Ue) at AC - max	690 V
Rated uninterrupted current (Iu)	160 A
Uninterrupted current	Rated uninterrupted current Iu is specified for max. cross-section.
Rated conditional short-circuit current (Iq)	30 kA
Rated short-time withstand current (Icw)	3 kA 3 kA, Contacts, 1 second
Short-circuit protection rating	160 A gG/gL, Fuse, Contacts
Load rating	1.6 x I# (with intermittent operation class 12, 40 % duty factor) 2 x I# (with intermittent operation class 12, 25 % duty factor) 1.3 x I# (with intermittent operation class 12, 60 % duty factor)
Number of contacts in series at DC-23A, 24 V	1
Number of contacts in series at DC-23A, 48 V	2
Number of contacts in series at DC-23A, 60 V	3

Number of contacts in series at DC-23A, 120 V		3
Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)		1600 A
Voltage per contact pair in series		42 V
Control circuit reliability		1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		1
Number of auxiliary contacts (normally open contacts)		1
Actuator color		Red
Actuator type		Door coupling rotary drive
Equipment heat dissipation, current-dependent Pvid		11 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		11 W
Rated operational current for specified heat dissipation (In)		160 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		UV resistance only in connection with protective shield.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Switch disconnector (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnector (ecl@ss10.0.1-27-37-14-03 [AKF060013])

Version as main switch		Yes
Version as maintenance-/service switch		Yes
Version as safety switch		No
Version as emergency stop installation		No
Version as reversing switch		No
Number of switches		1
Max. rated operation voltage Ue AC	V	690
Rated operating voltage	V	690 - 690
Rated permanent current Iu	A	160
Rated permanent current at AC-23, 400 V	A	105

Rated permanent current at AC-21, 400 V		A	160
Rated operation power at AC-3, 400 V		kW	45
Rated short-time withstand current Icw		kA	3
Rated operation power at AC-23, 400 V		kW	55
Switching power at 400 V		kW	55
Conditioned rated short-circuit current Iq		kA	30
Number of poles			6
Number of auxiliary contacts as normally closed contact			1
Number of auxiliary contacts as normally open contact			1
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Built-in device fixed built-in technique
Suitable for floor mounting			Yes
Suitable for front mounting 4-hole			No
Suitable for front mounting centre			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			Yes
Colour control element			Red
Type of control element			Door coupling rotary drive
Interlockable			Yes
Type of electrical connection of main circuit			Screw connection
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			12

© 04/2023 by Eaton Industries GmbH