Specifications

Eaton 098479



Catalog Number: 098479

Eaton xEnergy Safety Ci LV systems LV switchgear. Meter enclosure, HxWxD=500x375x225mm, IP65

General specifications

Product Name
Eaton xEnergy Safety Ci meter enclosure rail

Catalog Number
098479

EAN
4015080984795

Product Length/Depth
225 mm

Product Height
500 mm

Product Width
375 mm

Product Weight
8.2 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Special features

Meter rail to DIN 43853 including meter fixing screws and nuts Metric cable entry knockouts in all sides Fixing straps for wall fixing Sealable cover fasteners

Type

Ci insulated enclosure Meter enclosures Prepared enclosures

Features

Cover with overpressure release

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

Meets the product standard's requirements.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Lower part: 960 °C / cover: 850 °C

10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

10.2.5 Lifting

30 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.

10.2.6 Mechanical impact

IK10

10.2.7 Inscriptions

Meets the product standard's requirements.

Resources

Brochures

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-017.eps

eaton-enclosures-xenergy-safety-ci-lv-systems-dimensions-009.eps

eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-016.eps

eaton-distribution-boards-enclosure-xenergy-safety-ci-meter-enclosure-dimensions-005.eps

Installation instructions

05670392.pdf

System overview

eaton-distribution-boards-enclosure-xenergy-safety-ci-meter-enclosure-explosion-drawing.eps

10.3 Degree of protection of assemblies

IP65

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Protection class 2, therefore not applicable.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Ui = 1000 V AC

10.9.3 Impulse withstand voltage

8 kV

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Fitted with:

Mounting plate

Accessory/spare part type

Meter rail

Meter enclosures

Degree of protection

IP65

Other

IK10

Enclosure material

Plastic

Surface protection

Other

Circuit integrity

Other

Unit type

Complete housing

Built-in depth

200 mm

Heat diss. ambient 35°C delta T:20°C free stand individ. encl. top (IEC 60890)

40 W

Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890)

35 W

Heat diss. ambient 35°C delta T:20°C free stand starting encl. top (IEC 60890)

38 W

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)

36 W

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)

31 W

Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890)

33 W

Heat diss. ambient 35°C delta T:35°C free stand individ. encl. top (IEC 60890)

81 W

Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top (IEC 60890)

71 W

Heat diss. ambient 35°C delta T:35°C free stand starting encl. top (IEC 60890)

76 W

Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)

72 W

Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890)

62 W

Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890)

67 W

Color

Gray

Cover/door color

Transparent

Cover/door model

Closed

Cover/door type

Transparent

Optional

None

Number of openings (flange plates)

6

Plate thickness (cabinet)

6 mm

Plate thickness (cover/door)

6 mm

RAL-number

7035

Width in number of modular spacings

17

Mounting method

Surface mounted (plaster)

Number of rows

0

Functions

Extension possible

Protection class

II

Number of modules

1

Internal depth

200 mm

Mounting depth

186 mm

Nominal current

1600 A

Number of conduit inlets

104

Suitable for

Outdoor use

Lightning protection



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia