AUDIOLAN626

FLEXIBLE CABLE CAT.6 - F/UTP 6 250 MHZ

ADVANTAGES

- Highly flexible
- Reduce external diameter easy handling of the cable



1. Core : Flexible bare copper - AWG 26 - Multi-strand
2. Conductor insulation : PE - Ø 0.90 mm

Pair 1 : blue / white - blue
Pair 2 : orange / white - orange
Pair 3 : green / white - green
Pair 4 : brown / white - brown

3. Drain wire : Multi-strand tin-plated copper - Ø 0.40 mm
4. General shielding : Blue aluminium foil and polyester
5. Outer jacket : Black PVC - Ø 5.9 mm

DESCRIPTION / APPLICATIONS

- Transport of gigabit ethernet, Ethersound, Cobranet, Dante... signalsover twisted pair for links up to 110 m
- Ideal for all indoor and outdoor on-stage applications
- Compatible with CAT.5E

STANDARD

CONFORM EN50575 : 2014 + A1 : 2016
CAT.6 ACCORDING TO IEC 61156-6
CLASS : Eca
CONFORM WITH THE DIRECTIVE : RoHs

This document is confidential, and is the property of Multimedia Connect. Multimedia Connect own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from Multimedia Connect. The contents of this document must be disclosed to any other person or persons. The characteristics related to this document are not contractual, and can be modified without warning.

ELECTRICAL PROPERTIES

CONDUCTOR RESISTANCE : ≤ 290 MΩ/ km

INSULATION RESISTANCE : ≥ 5000 MΩ/ km

NOMINAL MUTATION CAPACITY : 1600 pF/ km

IMPEDANCE FROM 4 MHZ TO 250 MHZ : 100 Ω

ATTENUATIONS :

FREQUENCY MHZ	NOMINAL ATTENUATION DB / 100M	RETURN LOSS DB / 100M
1	3	20
10	9.9	20
100	38	25
250	49.9	25

MECANICAL AND TECHNICAL PROPERTIES

OPERATING TEMPERATURE: -30°C / +80°C

MINIMUM BEND OF RADIUS : 8 x Ø ext.

ORDER INFORMATION

PART NB	DESCRIPTION	OUTER DIAMETER	WEIGHT	PACKAGING
AUDIOLAN626	Flexible cable CAT.6 - F/UTP - 250 MHZ	5.9 mm	45 Kg/ Km	Custom length

This document is confidential, and is the property of Multimedia Connect. Multimedia Connect own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from Multimedia Connect. The contents of this document must be disclosed to any other person or persons. The characteristics related to this document are not contractual, and can be modified without warning.

ASSOCIATED PRODUCTS



Shielded PLUG RJ45 : MMCRJ45SC6SI



Neutrik Ethercon : NE8MX6



Crimp tool : MMCP86MET

This document is confidential, and is the property of Multimedia Connect. Multimedia Connect own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from Multimedia Connect. The contents of this document must be disclosed to any other person or persons. The characteristics related to this document are not contractual, and can be modified without warning.