Specifications

Eaton 266453



Catalog Number: 266453

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release, 480-525VAC/DC, 4

General specifications

Product Name
Eaton Moeller series NZM release

Catalog Number
266453

EAN
4015082664534

Product Length/Depth
107 mm

Product Height
51 mm

Product Width
64 mm

Product Weight
0.218 kg

Compliances
UL/CSA
IEC
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM4(-4), N(S)4(-4)

Type

Accessory
Shunt release

Special features

Switches are tripped by a voltage pulse or by the application of uninterrupted voltage.
If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.
Shunt releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XU... undervoltage release.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM4

eCAD model

DA-CE-ETN.NZM4-XA480-525AC_DC

Installation instructions

eaton-circuit-breaker-voltage-release-nzm4-il012143zu.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

Technical data sheets

eaton-nzm-technical-information-sheet

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Electric connection type

Screw connection

Frame

NZM4

Number of contacts (normally open contacts)

0

Rated control supply voltage (Us) at AC, 50 Hz - max

525 V

Rated control supply voltage (Us) at AC, 50 Hz - min

480 V

Rated control supply voltage (Us) at AC, 60 Hz - max

525 V

Rated control supply voltage (Us) at AC, 60 Hz - min

480 V

Suitable for

Off-load switch

Voltage type

AC

Rated control supply voltage (Us) at DC - max

525 V

Rated control supply voltage (Us) at DC - min

24 V

Number of contacts (normally closed contacts)

0

Number of contacts (change-over contacts)

0

Undelayed short-circuit release - min

0 A

Undelayed short-circuit release - max

0 A

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia