PRODUCT-DETAILS

# E217-16-10C

## Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, El. Color: Grey, 1LED, Red, MW: 0.5



### General Information

| | |
|---|---|
| Extended Product Type | E217-16-10C |
| Product ID | 2CCA703161R0001 |
| EAN | 7612270938995 |
| Catalog Description | Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, El. Color: Grey, 1LED, Red, MW: 0.5 |
| Long Description | Pushbutton 1 NO / 1 NC with maintenance-free LED, Rated current: 16A/250 VACPDC, LED colour: red, 115-250 VACPDC, 12-48 VACDCPDC, 110-220 VDCPDC, Module width 0,5 |

### Technical

| | |
|---|---|
| Standards | EN60068-2-1<br>EN60068-2-2<br>EN60068-2-30<br>DIN EN 60669-1<br>VDE 0632-1<br>UL508 |
| Rated Voltage ($U_r$) | Lamp 230 ... 250 V |
| Rated Operational Voltage | acc. to EN 250 V AC<br>acc. to UL 508 240 V AC |
| Voltage Range | 115 ... 250 V AC |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Auxiliary Voltage AC/DC | LED Indicator 115...250 V AC |
| Maximum Switching Voltage | 250 V |
| Rated Current ($I_n$) | 16 A |
| Rated Frequency (f) | 50/60 Hz |
| Power Loss | 1.1 W |
| Power Watt | 1.1 W |
| Number of Contacts NO | 1 |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 1 |
| Number of Auxiliary Contacts CO (SPDT) | 0 |
| Number of Poles | 1 |
| Number of LEDs | 1 |
| Tightening Torque | 1.2-1.5 N·m |
| Switch Type | Double Interrupting Contacts |
| Material of Conductor | Copper |
| Remarks | Sealable in the On and Off positions |
| Color | Red |
| Control Element Color | Grey |
| Lamp Color | Red |
| Connecting Capacity | Solid 1x1…6 mm²<br>Solid 2x2.5 mm²<br>Flexible 1x0.75…2x2.5 mm² |

## Material Compliance

| | |
|---|---|
| RoHS Information | 2CCC441014D0201 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20170426 |
| REACH Declaration | 2CCC005047D0201 |
| REACH Information | False - does not contain substances > 0.1 mass percentage |
| REACH Date | 20190425 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Operation -25...+55 °C<br>Storage -40...+70 °C |
| Degree of Protection | IP20 |
| Environmental Information | 2CCC441003C0201 |

## Dimensions

| | |
|---|---|
| Width in Number of Modular Spacings | 0.5 |
| Product Net Width | 9 mm |
| Product Net Height | 85 mm |
| Product Net Depth / Length | 68 mm |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Product Net Weight | 53 g |
| Built-In Depth ($t_2$) | 75 mm |

## Ordering

| | |
|---|---|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Gross Weight | 594 g |
| E-Number (Finland) | 2312333 |
| E-Number (Norway) | 1426438 |
| E-Number (Sweden) | 2102806 |
| E-Number (Switzerland) | 467552148 |

## Certificates and Declarations

| | |
|---|---|
| CB Certificate | 9AKK108466A3845 |
| CCC Certificate | 9AKK108466A3829 |
| Declaration of Conformity - CE | 2CCC441014D0201 |
| Declaration of Conformity - UKCA | 9AKK108467A6137 |
| VDE Certificate | 9AKK107991A9822 |

## Installation

| | |
|---|---|
| Instructions and Manuals | No document needed |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 2CCC441003C0101 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC001546 - Push button for distribution board |
| ETIM 9 | EC001546 - Push button for distribution board |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85365053 |
| UNSPSC | 39122216 |
| eClass | V11.0 : 27142302 |
| IDEA Granular Category Code (IGCC) | 5212 >> Push button for distribution board |
| Object Classification Code | S |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights → Switches, Pushbuttons and Indicator Lights, E210






360°

© 2024 ABB. All rights reserved.