*Date: 10/04/2023*

# PSD-4; 0...16 bar gauge ; one switching output (PNP/NPN) + 0...10 V

## PSD-4; 0...16 bar gauge ; one switching output (PNP/NPN) + 0...10 V

| | |
|---|---|
| Item number: | 48789424 |
| Quantity: | 1 pcs. |
| Order code: | PSD-4-BZ-BG416-GDZZ-WW-ZZ W1011PS4Z-SZAB-P-GSFI |
| Overview: | PSD-4; 0...16 bar gauge ; one switching output (PNP/NPN) + 0...10 V<br>Electronic pressure switch with display<br>Output signal: one switching output (PNP/NPN) + 0...10 V<br>IO-Link: without<br>Power supply: 15...35 V DC<br>Measuring range: 0...16 bar gauge<br>Process connection: G 1/2 B<br>Media temperature: -20 … 85 °C (-4 ... +185 °F)<br>El. connection: Circular connector M12x1 (4-pin)<br>pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4<br>Accuracy: ± 0.5% of span<br>Approvals: cULus<br>with test protocol<br>Specifications according to data sheet: PE 81.86 |
| Details: | PSD-4; 0...16 bar gauge ; one switching output (PNP/NPN) + 0...10 V<br>Electronic pressure switch with display<br>Output signal: one switching output (PNP/NPN) + 0...10 V<br>IO-Link: without<br>Power supply: 15...35 V DC<br>Measuring range: 0...16 bar gauge<br>Process connection: G 1/2 B<br>Media temperature: -20 … 85 °C (-4 ... +185 °F)<br>El. connection: Circular connector M12x1 (4-pin)<br>pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4<br>Accuracy: ± 0.5% of span<br>Approvals: cULus<br>with test protocol<br>Specifications according to data sheet: PE 81.86 |

*© 2023 - WIKA Instruments s.a.r.l.*