Specifications

Eaton 3-5027-005A

Catalog Number: 3-5027-005A

Eaton DM1 Variable frequency drive, 400 V AC, 3-phase, 12 A, 5.5 kW, IP20/NEMA0, Radio interference suppression filter, Brake chopper, FS2



General specifications

Product Name
Eaton DM1 Variable frequency drive

Catalog Number
3-5027-005A

EAN
4015081980451

Product Length/Depth
180 mm

Product Height
220 mm

Product Width
109 mm

Product Weight
2.6 kg

Certifications
UL 508C
EAC
IEC/EN61800-5
UL File No.: E134360
UL Listed
Certified by UL for use in Canada
IEC/EN61800-3
IEC/EN 61800-2
CUL
IEC/EN 61800-5-1
RoHS, ISO 9001
CE marking
CSA-C22.2 No. 274-13
C-Tick
CE
UkrSEPRO
IEC/EN 61800-3
CSA-C22.2 No. 274-17
UL Category Control No.: NMMS, NMMS7
UL

Powering Business Worldwide

General

Air volume capacity

64 m³/h

Cable length

C3 ≤ 25 m, maximum motor cable length

C2 ≤ 5 m, maximum motor cable length

Communication interface

SmartWire-DT, optional

DeviceNet, optional

PROFIBUS, optional

CANopen®, optional

Modbus RTU, built in

Connection to SmartWire-DT

Yes

In conjunction with DXG-NET-SWD SmartWire DT module

Degree of protection

IP20

NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Features

Temperature-controlled fan

Parameterization: Keypad

Parameterization: Power Xpert inControl

Parameterization: Fieldbus

Fitted with:

Radio interference suppression filter

Internal DC link

Brake chopper

IGBT inverter

Breaking resistance

PC connection

Frame size

FS2

Mounting position

Vertical

Number of slots

1 (expansion)

Climatic environmental conditions

Altitude

Max. 1000 m

Max. 3000 m

Max. 2000 m for Corner Grounded TN Systems

Above 1000 m with 1 % derating per 100 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Heat dissipation at current/speed

108 W at 50% current and 50% speed

120 W at 50% current and 90% speed

126 W at 100% current and 0% speed

169 W at 50% current and 0% speed

205 W at 100% current and 90% speed

71 W at 25% current and 0% speed

90 W at 100% current and 50% speed

94 W at 25% current and 50% speed

Input current ILN at 110% overload

19.2 A

Input current ILN at 150% overload

14.4 A

Mains current distortion

40 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
C1: with external filter, for conducted emissions only
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments

Safety function/level

STO (Safe Torque Off, SIL2, PLc Cat 2)

Shock resistance

0.75 mm (peak) at 10 - 57 Hz, max. 1 g at 57 - 150 Hz, according to EN 61800-5-1, EN 60068-2-6: 10 - 150 Hz

Suitable for

Branch circuits, (UL/CSA)

Mains voltage - min

380 V

Mains voltage - max

480 V

Operating mode

U/f control

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

480 V AC, 3-phase
400 V AC, 3-phase
500 V AC, 3-phase

Overload current IL at 110% overload

17.6 A

Overload current IL at 150% overload

18 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

16 A

Rated operational current (Ie) at 150% overload

12 A

Rated operational power at 380/400 V, 50 Hz, 110% overload

7.5 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase

5.5 kW

Rated operational power at 500 V, 50 Hz, 3-phase

5.5 kW

Rated operational power at 500 V, 50 Hz, 3-phase, 110% overload

7.5 kW

Rated operational voltage

500 V AC, 3-phase

480 V AC, 3-phase

400 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

20 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

4 kHz, 1 - 16 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

500 V

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

15.2 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

14 A

Assigned motor current IM at 500 V, 50 Hz, 110% overload

12.1 A

Assigned motor current IM at 500 V, 50 Hz, 150% overload

9 A

Assigned motor power at 460/480 V, 60 Hz

7.5 HP

Assigned motor power at 460/480 V, 60 Hz, 110% overload

10 HP

Braking function

Braking resistance

35 Ω

Braking torque

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Adjustable to 150 %, DC - Main circuit

Max. 30 % MN, Standard - Main circuit

Switch-on threshold for the braking transistor

800 VDC

Control circuit

Number of inputs (analog)

1

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of relay outputs

2 (parameterizable, 1 changeover contact and 1 N/O, 3 A (240 V AC) / 3 A (24 V DC))

Rated control voltage (Uc)

Design verification

Equipment heat dissipation, current-dependent Pvid

203 W

Rated operational current for specified heat dissipation (In)

16 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

24 V DC (external, max. 100 mA options incl.)

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Electromagnetic compatibility (EMC)

Dual Rating What exactly does that mean?

Connecting drives to generator supplies

Brochures

eaton-powerxl-dm1-variable-frequency-drives-brochure-br040016en-en-us.pdf

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004644.pdf

DA-DC-00004863.pdf

Installation instructions

DM1 IL PUB 53-675 TBG Change Request 12-24-21 Final (300 DPI).pdf

Installation videos

PowerXL Variable Frequency Drive DM1

Manuals and user guides

MN040049EN

MN040060EN

mCAD model

fs2-89-1327.stp

fs2_89_1327.dwg

Multimedia

PowerXL DM1 Variable Frequency Drive - Establishing a Modbus TCP connection with software Power Xper

PowerXL DM1 Variable Frequency Drive - Setup via WebUI

PowerXL DM1 Variable Frequency Drive - Setup via Software

PowerXL DM1 Variable Frequency Drive - Configuration with keypad

PowerXL DM1 Variable Frequency Drive - PowerXpert inControl with Bluetooth

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Sales notes

eaton-powerxl-dm1-variable-frequency-drives-flyer-fl040006en-en-us.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia