Bellows Couplings **HucoFlex K**


Huco Altra Industrial Motion


Bellows Coupling with removable clamp shaft connection, short version

ORDERING INFORMATION

RS PART No.	MANUFACTURER PART No.	BORES B1 & B2 [mm]
1967686	593.66.4646	19
1967687	593.66.4949	22
1967688	593.66.5252	23
1967690	593.66.5454	28
1967691	593.66.5858	32







DIMENSIONS & INTERFACE DATA

Overall Diameter D [mm]	66
Overall Length L [mm]	89
Maximum permissible bore B1. B2 [mm]	32
Length of supported bore L1 [mm]	29
Fastener thread size	M8
Fastener tightening torque [Nm]	40
Coupling approx weight [g]*	490

MATERIALS

Hubs	**Aluminium alloy**
Bellows	**Spring Quality Stainless Steel**
Fasteners	**Alloy Steel**

PERFORMANCE DATA

Maximum speed [min^{-1}]	8700
Peak Torque [Nm]	60
Maximum shaft angular misalignment [deg]	2
Maximum shaft radial misalignment [mm]	0.25
Maximum shaft axial displacement [mm]	1
Torsional Stiffness [$Nm.rad^{-1}$]	50000
Radial Stiffness [N/mm]	340
Axial Stiffness [N/mm]	50

Temperature Range

-30°C to +120°C

*weight with max. bore