Datasheet - PFB-IOP-4M12-IOP

Input expander / PFB



(Minor differences between the printed image and the original product may exist!)

- For parallel IO devices
- Passive field box for series-wiring
- For devices with M12 Connector, 8-pole
- For up to 4 safety switchgears
- Fuse protected device ports
- Heavy duty version for field installation
- Protection class IP67

Ordering details

Product type description	PFB-IOP-4M12-IOP
Article number	103013573
EAN code	
eCl@ss	

Approval

Approval	cULus USA/CAN

Global Properties

Product name	PFB
Application	
Standards	IEC 60947-1
Materials	
- Material of the housings	Plastic,
Weight	365 g

Mechanical data

Design of electrical connection	M12 connector socket / -Connector
restistance to shock	30 g / 11 ms

Resistance to vibration	10 … 150 Hz, Amplitude 0,35 mm

Ambient conditions

Ambient temperature	
- Min. environmental temperature	−20 °C
- Max. environmental temperature	+65 °C
Storage and transport temperature	
- Min. Storage and transport temperature	−40 °C
- Max. Storage and transport temperature	+70 °C
Relative humidity	10 … 95 %, non-condensing
Protection class	IP67
Protection rating	III
Insulation values to IEC 60664-1	
- Rated impulse withstand voltage U_{imp}	0,8 kV
- Rated insulation voltage U_i	32 VDC
- Overvoltage category	III
- Degree of pollution	3

Electrical data

Supply voltage U_B	24 VDC −15% / +10% (stabilised PELV)
Rated operating voltage U_e	24 VDC
Operating current I_e	
- Passive distribution module ()	10 A
- ()	1.5 A

LED switching conditions display

LED switching conditions display (Y/N)	Yes
Number of LED´s	9 piece

ATEX

Explosion protection Zones for gases	None
Explosion protection Zones for dusts	None

Dimensions

Dimensions	
- Width	63 mm
- Height	156.6 mm
- Depth	36.1 mm

Documents

Operating instructions (es) 785 kB, 29.08.2017
Code: mrl_pfb-iop-4m12-iop_es

Operating instructions (it) 783 kB, 11.09.2017
Code: mrl_pfb-iop-4m12-iop_it

Operating instructions (pt) 825 kB, 07.09.2017
Code: mrl_pfb-iop-4m12-iop_pt

Operating instructions (de) 821 kB, 27.07.2017
Code: mrl_pfb-iop-4m12-iop_de

Operating instructions (nl) 824 kB, 07.09.2017
Code: mrl_pfb-iop-4m12-iop_nl

Operating instructions (en) 821 kB, 27.07.2017
Code: mrl_pfb-iop-4m12-iop_en

Operating instructions (pl) 825 kB, 01.08.2017
Code: mrl_pfb-iop-4m12-iop_pl

Operating instructions (fr) 824 kB, 11.09.2017
Code: mrl_pfb-iop-4m12-iop_fr

Images



Product photo