Date: 24/04/2023

232.30.100 10 bar 1/2 NPT lower back mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 48800327

Quantity: 1 pcs.

Order code: 232.30-E-BG410Z-ND-3ZHZCZH-ZZZZZZZ 213D32ZF3W0 12Z-IZZZZZZ12ZZZ
LABEL-PG1DE-ZZZZZ

Overview:
232.30.100 10 bar 1/2 NPT lower back mount
Measuring System 316L
Ingress protection: IP 54
for oxygen, oil and grease free
class 1.0
Window: laminated safety glass
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
with thread protection
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number
Label: WIKA standard without / with Tag-number

Details:
Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 232.30
Specifications according to data sheet: PM 02.04
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Measuring range: gauge pressure range
Scale range: 0...10 bar
Process connection: 1/2 NPT
Connector location: lower back mount
Window: laminated safety glass
Pointer: standard pointer
Special design features: for oxygen, oil and grease free
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: no filling, not to fill
Ingress protection: IP 54
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.

Movement: stainless steel
Thread protection: with thread protection
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.