# DATASHEET - TM-1-8290/IVS

**ON-OFF switches, TM, 10 A, service distribution board mounting, 1 contact unit(s), Contacts: 1, 90 °, maintained, With 0 (Off) position, 0-1, Design number 8290**

**Part no.** **TM-1-8290/IVS**
**225334**

| | |
|---|---|
| Product name | Eaton Moeller® series TM On-Off switch |
| Part no. | TM-1-8290/IVS |
| EAN | 4015082253349 |
| Product Length/Depth | 65 millimetre |
| Product height | 60 millimetre |
| Product width | 35.5 millimetre |
| Product weight | 0.04 kilogram |
| Certifications | IEC/EN 60947-3<br>Certified by UL for use in Canada<br>UL report applies to both US and Canada<br>UL<br>UL 508<br>UL Category Control No.: NLRV<br>CSA-C22.2 No. 94<br>CSA<br>VDE 0660<br>CE<br>IEC/EN 60947-5-1<br>CSA-C22.2 No. 14-05<br>UL File No.: E36332<br>IEC/EN 60947 |
| Product Tradename | TM |
| Product Type | On-Off switch |
| Product Sub Type | None |
| | |
| Fitted with: | Black thumb grip and front plate |
| Inscription | 0-1 |
| Number of poles | 1 |
| | |
| Degree of protection | NEMA Other |
| Degree of protection (front side) | IP30 |
| Lifespan, mechanical | 1,000,000 Operations |
| Mounting method | Service distribution board mounting |
| Mounting position | As required |
| Number of contact units | 1 |
| Operating frequency | 1200 Operations/h |
| Overvoltage category | III |
| Pollution degree | 3 |
| Rated impulse withstand voltage (Uimp) | 4000 V AC |
| Suitable for | Ground mounting<br>Distribution board installation |
| Switching angle | 90 ° |
| Type | ON-OFF switch |
| | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 50 °C |
| Climatic proofing | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| | |
| Terminal capacity | 1 x 1.5 $mm^2$, flexible<br>2 x 1,5 $mm^2$, solid or stranded<br>1 x 1.0 $mm^2$, flexible with ferrules to DIN 46228<br>2 x 1.5 $mm^2$, flexible<br>2 x 1.0 $mm^2$, flexible with ferrules to DIN 46228<br>14 AWG, solid or flexible with ferrule |

| | |
|---|---|
| | 1 x 1.5 $mm^2$, solid or stranded |
| Screw size | M2.5, Terminal screw |
| Tightening torque | 0.4 Nm, Screw terminals<br>3.5 lb-in, Screw terminals |
| | |
| Rated operational power at AC-3, 380/400 V, 50 Hz | 0 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | 3 kW |
| Rated operational voltage (Ue) at AC - min | 500 V |
| Rated operational voltage (Ue) at AC - max | 500 V |
| Rated uninterrupted current (Iu) | 10 A |
| Uninterrupted current | Rated uninterrupted current Iu is specified for max. cross-section. |
| | |
| Rated conditional short-circuit current (Iq) | 0 kA |
| Rated short-time withstand current (Icw) | 0 kA |
| Short-circuit protection rating | 10 A gG/gL, Fuse, Contacts |
| | |
| Switching capacity (main contacts, general use) | 10 A, Rated uninterrupted current max. (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | 10A, IU, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | A300 (UL/CSA) |
| | |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | 0.33 HP |
| Assigned motor power at 115/120 V, 60 Hz, 3-phase | 0.75 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | 0.75 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | 1 HP |
| Assigned motor power at 277 V, 60 Hz, 1-phase | 0.75 HP |
| | |
| Control circuit reliability | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | 0 |
| Number of auxiliary contacts (normally closed contacts) | 0 |
| Number of auxiliary contacts (normally open contacts) | 0 |
| | |
| Actuator color | Black |
| Actuator function | Maintained<br>With 0 (Off) position |
| Actuator type | Short thumb-grip |
| | |
| Equipment heat dissipation, current-dependent Pvid | 0.15 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0.15 W |
| Rated operational current for specified heat dissipation (In) | 10 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |

| | | | |
|---|---|---|---|
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Switch disconnector (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnector (ecl@ss10.0.1-27-37-14-03 [AKF060013])

| | | | |
|---|---|---|---|
| Version as main switch | | | No |
| Version as maintenance-/service switch | | | No |
| Version as safety switch | | | No |
| Version as emergency stop installation | | | No |
| Version as reversing switch | | | No |
| Number of switches | | | 1 |
| Max. rated operation voltage Ue AC | | V | 500 |
| Rated operating voltage | | V | 500 - 500 |
| Rated permanent current Iu | | A | 10 |
| Rated permanent current at AC-23, 400 V | | A | 6.6 |
| Rated permanent current at AC-21, 400 V | | A | 0 |
| Rated operation power at AC-3, 400 V | | kW | 0 |
| Rated short-time withstand current Icw | | kA | 0 |
| Rated operation power at AC-23, 400 V | | kW | 3 |
| Switching power at 400 V | | kW | 0 |
| Conditioned rated short-circuit current Iq | | kA | 0 |
| Number of poles | | | 1 |
| Number of auxiliary contacts as normally closed contact | | | 0 |
| Number of auxiliary contacts as normally open contact | | | 0 |
| Number of auxiliary contacts as change-over contact | | | 0 |
| Motor drive optional | | | No |
| Motor drive integrated | | | No |
| Voltage release optional | | | No |
| Device construction | | | Built-in device fixed built-in technique |
| Suitable for floor mounting | | | Yes |
| Suitable for front mounting 4-hole | | | No |
| Suitable for front mounting centre | | | No |
| Suitable for distribution board installation | | | Yes |
| Suitable for intermediate mounting | | | No |
| Colour control element | | | Black |
| Type of control element | | | Short thumb-grip |
| Interlockable | | | No |
| Type of electrical connection of main circuit | | | Screw connection |
| Degree of protection (IP), front side | | | IP30 |
| Degree of protection (NEMA) | | | Other |


© 04/2023 by Eaton Industries GmbH