Specifications

Eaton 284730

Catalog Number: 284730

Eaton Distribution parts. Restarting device, 24-240V, 2HP



General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	284730
EAN	**Product Length/Depth**
4015082847302	80 mm
Product Height	**Product Width**
65.5 mm	35 mm
Product Weight	**Compliances**
0.076 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Restarting device - switching module
Accessory for miniature circuit breaker
Accessory
Accessory for residual current circuit breaker

Type

Accessory
Accessory for miniature
circuit breaker
Accessory for residual
current circuit breaker

Special features

24 V AC/DC - 230 V AC/DC (control voltage for remote testing)

Application

Switchgear for industrial and advanced commercial applications

Accessory/spare part type

Restarting device

Degree of protection

IP40

Frame

Standard front dimension: 45 mm

Equipment heat dissipation, current-dependent

0 W

Mounting method

Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715
For fitting on right to: Z-FW-LP, Z-FW-LPD

Additional equipment required

Remote release

Terminal protection

Protection against electric shock to A3, ÖVE-EN 6

Terminal type

Lift terminals

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-25 °C

Resources

Drawings

eaton-dimensions-mas-fw-mo.jpg

Installation instructions

IL019014ZU

mCAD model

z_fw_mo.stp

z_fw_mo.dwg

Wiring diagrams

FW_MO

Assembly width

2 TE

Enclosure width

80 mm

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

0

Number of poles at main contact unit - max

0

Number of switches (fault signal)

0

Rated operational current for specified heat dissipation (In)

0 A

Voltage type

AC

Functions

+ON/OFF/TEST

With auto test for earth leakage function

Remote release

Device fitting

Other

Mounting width

35 mm

Function selector

ON, OFF/RESET

Rated operational voltage (Ue) - max

230 V

Rated switch current

0 A

Relay output for tripping test

400 VAC

Static heat dissipation, non-current-dependent

5 W

Suitable for current of main contact unit - max

0 A

Terminal capacity (cable)

1.5 mm² (4x)

2.5 mm² (2x)

Terminal capacity (solid wire)

2.5 mm² (2x)

1.5 mm² (4x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia