RILEY READY READER™

The Riley Ready Reader is a sports style adjustable safety eyewear frame which is available in a range of magnifications from 1.00 to 3.00. The safety eyewear offers a comfortable and secure fit while providing additional magnification.









SPORTS STYLE



SOFT TEMPLE ENDS



SOFT TPE



INCLINABLE TEMPLES

KEY FEATURES

- Available in 1.00, 1.50, 2.00, 2.50 and 3.00 magnifications
- Adjustable ratchet to position reading lens
- Dual-injected temples for enhanced comfort
- Soft flexible nosebridge for comfortable and secure fit
- Sports wraparound styling to compliment plano safety eyewear

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
RILEY READY READER 1.00	RLY00510	2C-1.2 1FT CE +1.0	EN 166 FT UKCA CE	Impacts, UV radiations	ARIDA 400 Anti-scratch + Anti-fog / UV400 / Moisture repellent
RILEY READY READER 1.50	RLY00511	2C-1.2 1FT CE +1.5			
RILEY READY READER 2.00	RLY00512	2C-1.2 1FT CE +2.0			
RILEY READY READER 2.50	RLY00513	2C-1.2 1FT CE +2.5			
RILEY READY READER 3.00	RLY00514	2C-1.2 1FT CE +3.0			

RILEY READY READER™

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Adjustable ratchet to position reading lens
FRAME	Polycarbonate	Dual-injected temples for enhanced comfort
NOSE BRIDGE	Thermoplastic Rubber (TPR)	Soft flexible nosebridge for comfortable and secure fit
TEMPLE	Polycarbonate / Thermoplastic Elastomers (TPE)	Sports wraparound styling to compliment plano safety eyewear

LENS & FRAME MARKINGS

LENS MARKINGS

LENS FILTER TYPE:
2, 2C UV | **4** IR filter | **5, 6** Solar filter | **1.7 to 7** Welding filter if no shade number

SCALE NUMBER (SHADE):
1.2 Clear or Amber **1.4** Blue or I/O Waterproof
1.7 Minimises or I/O **2.5** Grey or Revo **3.1** Dark Grey or Mirror

Identity of manufacturer

OPTICAL CLASS:
1 High optical quality

MECHANICAL STRENGTH:
S Increased strength
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
A High energy impact, resists a 6mm, 0.86g ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:
8 Short circuit electric arc
9 Molten metal splash
K Resistance to scratches by fine particles
N Resistance to fogging

CE Certification mark

FRAME MARKINGS

Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:
S Increased strength
F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s
A High energy impact, resists a 6mm, 0.86 ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE
3 Liquid droplets or splashes
4 Large dust particles > 5 µm
5 Gases and small dust particles < 5 µm
8 Short circuit electric arc
9 Molten metal and hot solids

UKCA CE Certification marks

USA (ANSI)

LENS:
U6 UV (All lenses) **L1.3** LED **L1.7** Solar (I/O, Twilight)
L2.5 Solar (Grey) **L3** Solar (Dark Grey) **W4** Infrared lens

LENS AND FRAME:
Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

AUS (AS/NZS)

LENS MARKINGS:

OCULAR CATEGORY:
0 UV **1** Solar **2** Solar
3 Solar **O** Outdoor untinted

Certified Product Australian Standard™ Standard Mark (SAI Global)

MECHANICAL STRENGTH:
I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

FRAME MARKINGS:
AS/NZS 1337.1: 2010 guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by: UK - CCQS UK LTD. 25 Wilton Road, Pimlico, London, UK, SW1V 1LW [A.B. No. **1105**].
EU - CCQS Certification Services Limited., Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin 15 D15 AKK1, Ireland [N.B. No. **2834**]

Authorised Representative [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.

www.riley-eyewear.com

E: info@riley-eyewear.com
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK

Part of Globus GROUP

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

© 2022 Globus (Shetland) Ltd | RLY-DATA-READY-READER-0123_1