Specifications

Eaton 208283



Catalog Number: 208283

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/OE, 1 NCL, Side mounted, Screw terminals, DILM250 - DILH2600

General specifications

Product Name
Eaton Moeller® series DILM auxiliary contact module

Catalog Number
208283

EAN
4015082082833

Product Length/Depth
77 mm

Product Height
77 mm

Product Width
15 mm

Product Weight
0.04 kg

Certifications
CSA Class No.: 3211-04
UL
VDE 0660
UL Category Control No.: NKCR
CE
UL 508
IEC/EN 60947-4-1
CSA
CSA File No.: 012528
CSA-C22.2 No. 14-05
UL File No.: E29184
IEC/EN 60947

Catalog Notes
Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.

Powering Business Worldwide

Features Functions

Functions

For standard applications

Number of poles

Two-pole

Electric connection type

Screw connection

General

Degree of protection

IP20

Lifespan, electrical

1,300,000 Operations (at 230 V, AC-15, 3 A)

Model

Top mounting

Mounting method

Side mounting

Connection

Screw terminals

Overvoltage category

III

Pollution degree

3

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)

6000 V AC

6000 V

Type

Side-mounting auxiliary contacts

Climatic environmental conditions

Ambient operating temperature - min

-40 °C

Ambient operating temperature - max

60 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

Terminal capacities

Terminal capacity (flexible with ferrule)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

Terminal capacity (solid)

1 x (0.75 - 2.5) mm²

2 x (0.75 - 2.5) mm²

Terminal capacity (solid/stranded AWG)

18 - 14

Screw size

M3.5, Terminal screw, Control circuit cables

Screwdriver size

2, Terminal screw, Control circuit cables, Pozidriv screwdriver

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

Tightening torque

1.2 Nm, Screw terminals

Electrical rating

Rated operational current (Ie)

3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)

1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)

10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)

6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V

4 A

Rated operational current (Ie) at AC-15, 500 V

1.5 A

Rated operational current (Ie) at DC-13, 24 V

2 A

Rated operational current (Ie) at DC-13, 60 V

1.5 A

Rated operational current (Ie) at DC-13, 110 V

0.8 A

Rated operational current (Ie) at DC-13, 220 V, 230 V

0.3 A

Rated insulation voltage (Ui)

690 V

Rated operational voltage (Ue) at AC - max

500 V

Short-circuit rating

Rated conditional short-circuit current (Iq)

1 kA at 500 V

Short-circuit protection rating

Conventional thermal current Ith

Conventional thermal current ith at 60°C (3-pole, open)

10 A

Max. 16 A gG/gL, Fuse, Without welding, Auxiliary contacts FAZ-C4/1, Maximum overcurrent protective device, Short-circuit rating without welding, Short-circuit protection only, Contacts

Short-circuit protection rating without welding

16 A gG/gL, 500 V, Max. Fuse, Contacts

Switching capacity

Switching capacity (auxiliary contacts, general use)

1 A, 250 V DC, (UL/CSA)

15 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Contacts

Control circuit reliability

$\lambda < 5 \times 1/10^{7}$ (1 failure at 2,000,000 operations for U_e = 24 V DC, Umin = 17 V, Imin = 5.4 mA)

Number of contacts

1 (normally open, early make)

1 (normally closed, late break)

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

1

Safety

Safe isolation

440 V AC, Between auxiliary contacts, According to EN 61140

440 V AC, Between auxiliary contacts and main contacts, According to EN 61140

440 V AC, Between coil and auxiliary contacts, According to EN 61140

Design verification

Equipment heat dissipation, current-dependent Pvid

0.25 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0.11 W

Rated operational current for specified heat dissipation (In)

6 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Resources

Catalogs

Product Range Catalog Switching and protecting motors

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

SmartWire-DT Catalog

Declarations of conformity

DA-DC-00004798.pdf

DA-DC-00005052.pdf

DA-DC-00004669.pdf

DA-DC-00004670.pdf

DA-DC-00004796.pdf

DA-DC-00004803.pdf

DA-DC-00005043.pdf

DA-DC-00004804.pdf

Drawings

eaton-contactors-module-dilm-accessory-3d-drawing.eps

eCAD model

ETN.DILM820-XHI11V-SI

Installation instructions

IL034037ZU

IL034095ZU

Installation videos

WIN-WIN with push-in technology

mCAD model

dil_m32_xhi11_s

dil_m32_xhi11_s.stp

Wiring diagrams

eaton-contactors-mounting-dilm-accessory-wiring-diagram-002.eps

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia