
# DATASHEET - DILM185A/22(RDC24)





**Contactor, 380 V 400 V 90 kW, 2 N/O, 2 NC, RDC 24: 24 - 27 V DC, DC operation, Screw connection**

Powering Business Worldwide™

| | |
|---|---|
| **Part no.** | **DILM185A/22(RDC24)** |
| **Catalog No.** | **139540** |
| **Alternate Catalog No.** | **XTCE185H22TD** |
| **EL-Nummer (Norway)** | **4134280** |


## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Contactors |
| Application | | | Contactors for Motors |
| Subrange | | | Standard devices greater than 170 A |
| Utilization category | | | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>NAC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Connection technique | | | Screw connection |
| **Rated operational current** | | | |
| AC-3 | | | |
| 380 V 400 V | $I_e$ | A | 185 |
| AC-1 | | | |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz | | | |
| Open | | | |
| at 40 °C | $I_{th} = I_e$ | A | 337 |
| enclosed | $I_{th}$ | A | 245 |
| Conventional free air thermal current, 1 pole | | | |
| open | $I_{th}$ | A | 688 |
| enclosed | $I_{th}$ | A | 613 |
| **Max. rating for three-phase motors, 50 - 60 Hz** | | | |
| AC-3 | | | |
| 220 V 230 V | P | kW | 55 |
| 380 V 400 V | P | kW | 90 |
| 660 V 690 V | P | kW | 140 |
| 1000 V | P | kW | 108 |
| AC-4 | | | |
| 220 V 230 V | P | kW | 41 |
| 380 V 400 V | P | kW | 75 |
| 660 V 690 V | P | kW | 102 |
| 1000 V | P | kW | 77 |
| Contact sequence | | |  |
| Can be combined with auxiliary contact | | | DILM1000-XHI… |
| Actuating voltage | | | RDC 24: 24 - 27 V DC |
| Voltage AC/DC | | | DC operation |
| **Contacts** | | | |
| N/O = Normally open | | | 2 N/O |
| N/C = Normally closed | | | 2 NC |
| **Auxiliary contacts** | | | |
| possible variants at auxiliary contact module fitting options | | | on the side: 2 x DILM1000-XHI(V)11-SI; 2 x DILM1000-XHI11-SA |
| Side mounting auxiliary contacts | | |  |

| | | | |
|---|---|---|---|
| **Instructions** | | | Interlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module<br>Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open) |
| **Instructions** | | | integrated suppressor circuit in actuating electronics<br>660 V, 690 V or 1000 V: not directly reversing |

# Technical data

## General

| | | | |
|---|---|---|---|
| Standards | | | IEC/EN 60947, VDE 0660, UL, CSA |
| Lifespan, mechanical | | | |
| DC operated | Operations | x $10^6$ | 10 |
| Operating frequency, mechanical | | | |
| DC operated | Operations/h | | 3000 |
| Climatic proofing | | | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature | | | |
| Open | | °C | -40 - +60 |
| Enclosed | | °C | - 40 - + 40 |
| Storage | | °C | - 40 - + 80 |
| Mounting position | | |  |
| Mechanical shock resistance (IEC/EN 60068-2-27) | | | |
| Half-sinusoidal shock, 10 ms | | | |
| Main contacts | | | |
| N/O contact | | g | 10 |
| Auxiliary contacts | | | |
| N/O contact | | g | 10 |
| N/C contact | | g | 8 |
| Degree of Protection | | | IP00 |
| Protection against direct contact when actuated from front (EN 50274) | | | Finger and back-of-hand proof with terminal shroud or terminal block |
| Altitude | | m | Max. 2000 |
| Weight | | | |
| AC operated | | kg | 3.54 |
| DC operated | | kg | 3.54 |
| Weight | | kg | 3.54 |
| Terminal capacity main cable | | | |
| Flexible with cable lug | | $mm^2$ | 50 - 185 |
| Stranded with cable lug | | $mm^2$ | 50 - 185 |
| Solid or stranded | | AWG | 1/0 - 350 MCM |
| Flat conductor | Lamellenzahl x Breite x Dicke | mm | Fixing with flat cable terminal or cable terminal blocks<br>See terminal capacity for cable terminal blocks |
| Busbar | Width | mm | 32 |
| Main cable connection screw/bolt | | | M10 |
| Tightening torque | | Nm | 24 |
| Terminal capacity control circuit cables | | | |
| Solid | | $mm^2$ | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Flexible with ferrule | | $mm^2$ | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Solid or stranded | | AWG | 18 - 14 |
| Control circuit cable connection screw/bolt | | | M3.5 |
| Tightening torque | | Nm | 1.2 |
| Tool | | | |

| | | | |
|---|---|---|---|
| Main cable | | | |
| Width across flats | | mm | 16 |
| Control circuit cables | | | |
| Pozidriv screwdriver | | Size | 2 |

## Main conducting paths

| | | | |
|---|---|---|---|
| Rated impulse withstand voltage | $U_{imp}$ | V AC | 8000 |
| Overvoltage category/pollution degree | | | III/3 |
| Rated insulation voltage | $U_i$ | V AC | 1000 |
| Rated operational voltage | $U_e$ | V AC | 1000 |
| Safe isolation to EN 61140 | | | |
| between coil and contacts | | V AC | 1000 |
| between the contacts | | V AC | 1000 |
| Making capacity (p.f. to IEC/EN 60947) | | A | 2700 |
| Breaking capacity | | | |
| 220 V 230 V | | A | 2250 |
| 380 V 400 V | | A | 2250 |
| 500 V | | A | 2250 |
| 660 V 690 V | | A | 2250 |
| 1000 V | | A | 760 |
| Component lifespan | | | |
| | | | AC1: See → Engineering, characteristic curves<br>AC3: See → Engineering, characteristic curves<br>AC4: See → Engineering, characteristic curves |
| Short-circuit rating | | | |
| Short-circuit protection maximum fuse | | | |
| Type “2” coordination | | | |
| 400 V | gG/gL 500 V | A | 315 |
| 690 V | gG/gL 690 V | A | 250 |
| 1000 V | gG/gL 1000 V | A | 160 |
| Type “1” coordination | | | |
| 400 V | gG/gL 500 V | A | 400 |
| 690 V | gG/gL 690 V | A | 315 |
| 1000 V | gG/gL 1000 V | A | 200 |

## AC

| | | | |
|---|---|---|---|
| AC-1 | | | |
| Rated operational current | | | |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz | | | |
| Open | | | |
| at 40 °C | $I_{th} = I_e$ | A | 337 |
| at 50 °C | $I_{th} = I_e$ | A | 301 |
| at 55 °C | $I_{th} = I_e$ | A | 287 |
| at 60 °C | $I_{th} = I_e$ | A | 275 |
| enclosed | $I_{th}$ | A | 245 |
| Notes | | | At maximum permissible ambient air temperature. |
| Conventional free air thermal current, 1 pole | | | |
| Note | | | at maximum permissible ambient air temperature |
| open | $I_{th}$ | A | 688 |
| enclosed | $I_{th}$ | A | 613 |
| AC-3 | | | |
| Rated operational current | | | |
| Open, 3-pole: 50 – 60 Hz | | | |
| Notes | | | At maximum permissible ambient temperature (open.) |
| 220 V 230 V | $I_e$ | A | 185 |
| 240 V | $I_e$ | A | 185 |
| 380 V 400 V | $I_e$ | A | 185 |

| | | | |
|---|---|---|---|
| 415 V | $I_e$ | A | 185 |
| 440V | $I_e$ | A | 185 |
| 500 V | $I_e$ | A | 185 |
| 660 V 690 V | $I_e$ | A | 150 |
| 1000 V | $I_e$ | A | 76 |
| Motor rating | P | kWh | |
| 220 V 230 V | P | kW | 55 |
| 240V | P | kW | 62 |
| 380 V 400 V | P | kW | 90 |
| 415 V | P | kW | 110 |
| 440 V | P | kW | 115 |
| 500 V | P | kW | 132 |
| 660 V 690 V | P | kW | 140 |
| 1000 V | P | kW | 108 |
| AC-4 | | | |
| Rated operational current | | | |
| Open, 3-pole: 50 – 60 Hz | | | |
| 220 V 230 V | $I_e$ | A | 136 |
| 240 V | $I_e$ | A | 136 |
| 380 V 400 V | $I_e$ | A | 136 |
| 415 V | $I_e$ | A | 136 |
| 440 V | $I_e$ | A | 136 |
| 500 V | $I_e$ | A | 136 |
| 660 V 690 V | $I_e$ | A | 110 |
| 1000 V | $I_e$ | A | 55 |
| Motor rating | P | kWh | |
| 220 V 230 V | P | kW | 41 |
| 240 V | P | kW | 45 |
| 380 V 400 V | P | kW | 75 |
| 415 V | P | kW | 80 |
| 440 V | P | kW | 85 |
| 500 V | P | kW | 96 |
| 660 V 690 V | P | kW | 102 |
| 1000 V | P | kW | 77 |

## Condensor operation

| | | | |
|---|---|---|---|
| Individual compensation, rated operational current $I_e$ of three-phase capacitors | | | |
| Open | | | |
| up to 525 V | | A | 220 |
| 690 V | | A | 133 |
| Max. inrush current peak | | x $I_e$ | 30 |
| Component lifespan | Operations | x $10^6$ | 0.1 |
| Max. operating frequency | | Ops/h | 200 |

## DC

| | | | |
|---|---|---|---|
| Rated operational current, open | | | |
| DC-1 | | | |
| Notes | | | see DILDC300/DILDC600 or on request |

## Current heat loss

| | | | |
|---|---|---|---|
| 3 pole, at $I_{th}$ (60°) | | W | 34 |
| Current heat loss at $I_e$ to AC-3/400 V | | W | 16 |
| Impedance per pole | | mΩ | 0.15 |

## Magnet systems

| | | | |
|---|---|---|---|
| Voltage tolerance | | | |
| $U_S$ | | | 24 - 27 V DC |
| DC operated | Pick-up | | 0.7 x $U_{S\ min}$ - 1.2 x $U_{S\ max}$ |

| | | | |
|---|---|---|---|
| DC operated | Drop-out | | 0.15 x $U_{S\ min}$ - 0.6 x $U_{S\ max}$ |
| Power consumption of the coil in a cold state and 1.0 x $U_S$ | | | |
| Pull-in power | Pick-up | VA | 210 |
| Pull-in power | Pick-up | W | 180 |
| Sealing power | Sealing | W | 2.1 |
| Duty factor | | % DF | 100 |
| Changeover time at 100 % $U_S$ (recommended value) | | | |
| Main contacts | | | |
| Closing delay | | ms | 60 |
| Opening delay | | ms | 40 |

## Electromagnetic compatibility (EMC)

| | | | |
|---|---|---|---|
| Electromagnetic compatibility | | | This product is designed for operation in industrial environments (environment A). Its use in residential environments (environment B) may cause radio-frequency interference, requiring additional noise suppression measures. |

## Rating data for approved types

| | | | |
|---|---|---|---|
| Switching capacity | | | |
| Maximum motor rating | | | |
| Three-phase | | | |
| 200 V<br>208 V | | HP | 50 |
| 230 V<br>240 V | | HP | 60 |
| 460 V<br>480 V | | HP | 125 |
| 575 V<br>600 V | | HP | 150 |
| General use | | A | 250 |
| Auxiliary contacts | | | |
| Pilot Duty | | | |
| AC operated | | | A600 |
| DC operated | | | P300 |
| General Use | | | |
| AC | | V | 600 |
| AC | | A | 15 |
| DC | | V | 250 |
| DC | | A | 1 |
| Short Circuit Current Rating | | SCCR | |
| Basic Rating | | | |
| SCCR | | kA | 10 |
| max. Fuse | | A | 700 |
| max. CB | | A | 800 |
| 480 V High Fault | | | |
| SCCR (fuse) | | kA | 100 |
| max. Fuse | | A | 600 Class J |
| SCCR (CB) | | kA | 65 |
| max. CB | | A | 350 |
| 600 V High Fault | | | |
| SCCR (fuse) | | kA | 100 |
| max. Fuse | | A | 600 Class J |
| SCCR (CB) | | kA | 50 |
| max. CB | | A | 350 |
| Special Purpose Ratings | | | |
| Definite Purpose Ratings (100,000 cycles acc. to UL 1995) | | | |
| LRA 480V 60Hz 3phase | | A | 2016 |
| FLA 480V 60Hz 3phase | | A | 336 |
| LRA 600V 60Hz 3phase | | A | 1680 |
| FLA 600V 60Hz 3phase | | A | 280 |

## Design verification as per IEC/EN 61439

| | | | |
|---|---|---|---|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | $I_n$ | A | 185 |
| Heat dissipation per pole, current-dependent | $P_{vid}$ | W | 5.33 |
| Equipment heat dissipation, current-dependent | $P_{vid}$ | W | 0 |
| Static heat dissipation, non-current-dependent | $P_{vs}$ | W | 2.1 |
| Heat dissipation capacity | $P_{diss}$ | W | 0 |
| Operating ambient temperature min. | | °C | -40 |
| Operating ambient temperature max. | | °C | 60 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0


| | | | |
|---|---|---|---|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) | | | |
| Rated control supply voltage Us at AC 50HZ | | V | 0 - 0 |
| Rated control supply voltage Us at AC 60HZ | | V | 0 - 0 |
| Rated control supply voltage Us at DC | | V | 24 - 27 |
| Voltage type for actuating | | | DC |
| Rated operation current Ie at AC-1, 400 V | | A | 337 |
| Rated operation current Ie at AC-3, 400 V | | A | 185 |
| Rated operation power at AC-3, 400 V | | kW | 90 |
| Rated operation current Ie at AC-4, 400 V | | A | 136 |
| Rated operation power at AC-4, 400 V | | kW | 75 |
| Rated operation power NEMA | | kW | 93 |
| Modular version | | | No |
| Number of auxiliary contacts as normally open contact | | | 2 |
| Number of auxiliary contacts as normally closed contact | | | 2 |
| Type of electrical connection of main circuit | | | Rail connection |
| Number of normally closed contacts as main contact | | | 0 |

| | | |
|---|---|---|
| Number of normally open contacts as main contact | | 3 |


## Approvals

| | | |
|---|---|---|
| Product Standards | | IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking |
| UL File No. | | E29096 |
| UL Category Control No. | | NLDX |
| CSA File No. | | 2389068 |
| CSA Class No. | | 3211-04 |
| North America Certification | | UL listed, CSA certified |
| Specially designed for North America | | No |


## Characteristics





on the side: 2 x DILM1000-XHI(V)11-SI; 2 x DILM1000-XHI11-SA





Normal switching duty
Normal AC induction motor
Operating characteristics
Switch on: from stop
Switch off: during run
Electrical characteristics:
Switch on: up to 6 x Rated motor current
Switch off: up to 1 x Rated motor current
Utility category
100 % AC-3
Typical Applications
Compressors
Lifts
Mixers
Pumps
Escalators
Agitators
fan
Conveyor belts
Centrifuges
Hinged flaps
Bucket-elevator
Air-conditioning systems
General drives for manufacturing and processing machines




Extreme switching duty
Squirrel-cage motor
Operating characteristics
Inching, plugging, reversing
Electrical characteristics
Make: up to 6 x rated motor current
Break: up to 6 x rated motor current
Utilization category
100 % AC-4
Typical applications
Printing presses
Wire-drawing machines
Centrifuges
Special drives for manufacturing and processing machines





Switching conditions for 3 pole, non-motor loads
Operating characteristics
Non inductive and slightly inductive loads
Electrical characteristics
Switch on: 1 x rated operational current
Switch off: 1 x rated operational current
Utilization category
100 % AC-1
Typical examples of application
Electric heat




Short-time loading, 3-pole
Time interval between two loading cycles: 15 minutes

## Dimensions




① DILM1000-XHI(V)11-SI
② DILM1000-XHI11-SA

DILM185…DILM500
DILMC185-S…DILMC500-S
DILM185-S…DILM500-S

## Additional product information (links)

| IL03406001Z Contactors | |
|---|---|
| IL03406001Z Contactors | https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03406001Z2021_08.pdf |
| Motor starters and "Special Purpose Ratings" for the North American market | http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf |
| Switchgear of Power Factor Correction Systems | http://www.moeller.net/binary/ver_techpapers/ver934en.pdf |
| X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely | http://www.moeller.net/binary/ver_techpapers/ver938en.pdf |
| Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions | http://www.moeller.net/binary/ver_techpapers/ver944en.pdf |
| Effect of the Cabel Capacitance of Long Control Cables on the Actuation of Contactors | http://www.moeller.net/binary/ver_techpapers/ver949en.pdf |
| Switchgear for Luminaires | http://www.moeller.net/binary/ver_techpapers/ver955en.pdf |
| Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts | http://www.moeller.net/binary/ver_techpapers/ver956en.pdf |
| The Interaction of Contactors with PLCs | http://www.moeller.net/binary/ver_techpapers/ver957en.pdf |
| Busbar Component Adapters for modern Industrial control panels | http://www.moeller.net/binary/ver_techpapers/ver960en.pdf |


© 07/2022 by Eaton Industries GmbH