Date: 17/04/2023

TR11-C, 2xPt100, 3-w, Cl.A, -30/250°C (F), terminal block, Removable

TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Item number:	48798058
Quantity:	1 pcs.
Order code:	TR11-C-ZZZZ-23HT-CZ1A-ZZ-ATGGDL90075ZZZ10103-ZZZZR12 011330LZ-ZA-Z-WIKA0-ZZ
Overview:	TR11-C, 2xPt100, 3-w, Cl.A, -30/250°C (F), terminal block, Removable Diameter measuring insert: 3 mm Stainless steel 316L Head / housing: BSS (Alu), Strd.-gland, M20 x 1.5 Transmitter: Without (terminal block) Protection tube: Straight, thread 316L, Ø 6x1 mm, M24 x 1,5 - G1/2B, MH=Without U1=75 mm Sealing: Without Specifications according to data sheet: TE 60.03 Measuring insert length (spare) [l5]: 113 mm Protection tube total length (spare) [L]: 103 mm Thermowell specials: Without
Details:	TR11-C RTD assembly with fabricated threaded protection tube (tubing) Specifications according to data sheet: TE 60.03 2xPt100, 3-wire Class A, IEC 60751 Temperature range of selected class: -30...+250°C BSS, Aluminum, ball shaped, flip-top, locking lever Cable entry: Standard cable entry Thread size cable entry: M20 x 1.5 Transmitter: Without (terminal block) Protection tube: Straight, thread Connection to neck tube: M24 x 1,5 Protection tube diameter: 6x1 mm Protection tube material: Stainless steel 316L Process connection: G 1/2 B Insertion length [A] [U1]: 75 mm Neck length [MH/N]: Without Material measuring insert: Stainless steel 316L Sealing: Without Measuring insert: Removable

© 2023 - WIKA Instruments s.a.r.l.

Diameter measuring insert: 3 mm
Thermowell specials: Without

© 2023 - WIKA Instruments s.a.r.l.