PRODUCT-DETAILS

ZLS202

ZLS202 Busbar



General Information

Extended Product Type	ZLS202
Product ID	2CCF002773R0001
EAN	7612270015719
Catalog Description	ZLS202 Busbar
Long Description	Auxiliary Busbar 5 x 2 mm, for LA and LB galvanic plated for SMISSLINE TP-Touch proof system Delivery length 1979 mm 110PLE

Technical

Standards	IEC/EN 61439-6
Product Name	Busbar
Type of Residual Current	standard version
Rated Operational Voltage	690/1000 V AC/DC
Rated Current (I_n)	40 A
Options Provided	Busbar LA,LB
Model Number	Flat

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	2CCY451206D0201

Dimensions

Product Net Width	10 mm
Product Net Height	5 mm
Product Net Depth / Length	1980 mm
Product Net Weight	179 g
Product Net Length	1979 mm

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	55 mm
Package Level 1 Height	19 mm
Package Level 1 Depth / Length	1990 mm
Package Level 1 Gross Weight	1199 g
Package Level 1 EAN	7612270015719

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389040
E-Number (Finland)	3210892
E-Number (Sweden)	2100075
E-Number (Switzerland)	809998015
Country of Origin	Switzerland (CH)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107991A9646
Environmental Information	2CCY451206D0201
Instructions and Manuals	9AKK107680A2315
RoHS Information	9AKK107991A9646

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
Instructions and Manuals	9AKK107680A2315
Dimension Diagram	9AKK107492A6192

Classifications

ETIM 6	EC001522 - Busbar
ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar
EPLAN Catalog Tree	Mechanics / Busbars / General
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

CN8	85389040
Object Classification Code	W

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A

