*Date: 13/04/2023*

# RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)

RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)

| | |
|---|---|
| Item number: | 48799957 |
| Quantity: | 1 pcs. |
| Order code: | RLS-30004M103050ZZZZZZZZZZZZZ3ZZZZZ1GZ8M035004Z3<br>Z1W101ARS3ZL6 |
| Overview: | RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)<br>Magnetic float switch with temperature output Model RLS-3000<br>Output signal level: 1 switching output<br>max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A<br>max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A<br>Unit of measure switching position: mm<br>Switching function - Switch output 1 : Normally closed / n.c.<br>Switch position - Switch output 1 : 305.0<br>Switch position - Switch output 2: without<br>Switch position - Switch output 3: without<br>Output signal temperature: Pt100 (2-wire)<br>Electrical connection: Circular connector M12x1, IP65<br>pin assignment el. connection: see product label<br>Process connection: G 1, installation from outside<br>Guide tube length: 350 mm mm<br>medium temperature: -30 °C ... 80 °C<br>Float: Cylindrical float Ø 30 mm, 1.4571, PN10<br>Wetted parts: Stainless steel 1.4571<br>Specifications according to data sheet: LM 50.06 |
| Details: | RLS-3000; Guide tube length: 350 mm; 1 switching output; Pt100 (2-wire)<br>Magnetic float switch with temperature output Model RLS-3000<br>Output signal level: 1 switching output<br>max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A<br>max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A<br>Unit of measure switching position: mm<br>Switching function - Switch output 1 : Normally closed / n.c.<br>Switch position - Switch output 1 : 305.0<br>Switch position - Switch output 2: without<br>Switch position - Switch output 3: without<br>Output signal temperature: Pt100 (2-wire)<br>Electrical connection: Circular connector M12x1, IP65<br>pin assignment el. connection: see product label |

*© 2023 - WIKA Instruments s.a.r.l.*

Process connection: G 1, installation from outside
Guide tube length: 350 mm mm
medium temperature: -30 °C ... 80 °C
Float: Cylindrical float Ø 30 mm, 1.4571, PN10
Wetted parts: Stainless steel 1.4571
Specifications according to data sheet: LM 50.06

*© 2023 - WIKA Instruments s.a.r.l.*