Product

AKL 3-g



Entries

Entries end:
15 x M20
2 x M20/M25
1 x M32/M40
Entries on each side:
12 x M20
3 x M25/M32

Empty Enclosure, with attachment bushes, sealing and insulating plugs, base and cover: polystyrene, grey, similar to RAL 7035

Article: AKL 3-g

Technical Data

Dimensions:

Width:	300 mm
Length:	450 mm
Height:	132 mm

material:

Base:	Polystyrene, grey, similar to RAL 7035
Cover:	Polystyrene, grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Properties:

Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short	{50%}

All information is provided without warranty. We reserve the right to make improvements in the interest of technical progress.

Therm):	
Rated insulation voltage AC:	690 V
Impact restistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
Halogen-free:	√
PVC-free:	√
Heavy metals-free:	√
Silicone-free:	√
UV resistance:	-
Combustion behaviour to UL:	HB acc. UL94
Combustion behaviour to VDE:	650°C acc. VDE 0471/ EN 60695
Knockouts:	√

All information is provided without warranty. We reserve the right to make improvements in the interest of technical progress.

Manufacturer

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1
58579 Schalksmühle
+49 (0)2355/892-0
+49 (0)2355/892-299
www.spelsberg.de

All information is provided without warranty. We reserve the right to make improvements in the interest of technical progress.