Specifications

Eaton 186174



Catalog Number: 186174

Eaton Moeller® series C22 Changeover switch, With thumb-grip, momentary, 2 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, Bezel: titanium

General specifications

Product Name
Eaton Moeller® series C22 Changeover switch

Catalog Number
186174

EAN
4015081816750

Product Length/Depth
3576 mm

Product Height
30 mm

Product Width
30 mm

Product Weight
0.122 kg

Certifications
IEC/EN 60947-5-1
CE
UL
VDE 0660
CSA
CSA File No.: 165628
CSA Class No.: 321103
UL File No.: E29184
UL 508
CSA-C22.2 No. 14-18 and No. 94.2-15
CE marking
UL Category Control No.: NKCR
UL listed, CSA certified

Catalog Notes
Contacts with safety function, by positive opening to IEC/EN 60947-5-1

Powering Business Worldwide

Product specifications

Type
Selector switch actuator

Actuator color
Black

Product Category
RMQ compact solution

Actuator function
Spring-return
Momentary

Electric connection type
Other

Fitted with:
Front ring

Operating frequency
2000 Operations/h

Pollution degree
3

Climatic proofing
Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT
No

Rated impulse withstand voltage (Uimp)
800 V AC

Actuator type
Toggle

Actuator diameter
4.7 mm

Actuator travel and actuation force (DIN EN 60947-5-1)
4.65 mm

Ambient operating temperature - max
70 °C

Ambient operating temperature - min
-30 °C

Force for positive opening - min
30 N

Resources

Catalogs
eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity
DA-DC-00004135.pdf

DA-DC-00004157.pdf

Drawings
eaton-operating-c22-changeover-switch-dimensions.eps

eaton-operating-c22-changeover-switch-3d-drawing.eps

eCAD model
DA-CE-ETN.C22-WK-K02-P65

Installation instructions
IL047016ZU

Installation videos
Eaton's RMQ compact solution pilot devices

mCAD model
DA-CD-c22_w_open_cable

DA-CS-c22_w_open_cable

Sales notes
eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

System overview
Pilot devices - selection aid

Wiring diagrams
eaton-operating-c22-pushbutton-wiring-diagram-004.eps

Knob travel

5.7 mm

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

2

Number of contacts (normally open contacts)

0

Opening diameter

22.5 mm

Opening height

0 mm

Operating torque

0.3 Nm

Rated insulation voltage (Ui)

250 V

Rated operational current (Ie) at AC-15, 24 V

4 A

Rated operational current (Ie) at DC-13, 24 V

3 A

Bezel color

Titanium

Cable material

PUR

Bezel material

Plastic

Design

Cable end open

With thumb-grip

Classical

Mounting position

As required

Rated conditional short-circuit current (Iq)

1 kA

Cable length

3.5 m

Connection type

Cable (black) with non-terminated end, 4 pole

Overvoltage category

III

Control circuit reliability

1 failure per 900,000 switching operations statistically determined, at 17 V DC/7 mA: N/C contact)

Degree of protection

IP66

IP65, rear

NEMA Other

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Number of switch positions

2

Tightening torque

2 Nm, Threaded ring

Short-circuit protection rating

Max. 4 A gG/gL, Fuse, Contacts

Supply voltage - max

0 V

Supply voltage - min

0 V

Switching angle

40 °

Width opening

0 mm

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.