Specifications

Eaton 193176



Catalog Number: 193176

Eaton xEnergy Basic LV systems Low voltage switchgear. Surface-mounted installation distributor IP31, EP, WxHxD=850x860x250mm, white, twist lock

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic empty enclosure	193176
EAN	**Product Length/Depth**
9010238008373	250 mm
Product Height	**Product Width**
860 mm	850 mm
Product Weight	**Compliances**
24.4 kg	RoHS conform

Powering Business Worldwide

Product specifications

Type

Basic device

Features

Connectable

Mounting plate depth-adjustable

EMC-version

Surface finishing

Powder coating

Degree of protection

IP31

IK08 (impact resistance)

Other

Grade material

Sheet steel

Material quality

Other

Color

White

Permissible load of the mounting plate according to IEC 62208 - max

0 N

Number of locks

0

RAL-number

9016

Material

Steel

Sheet steel

Mounting method

Wall fastening

Surface mounting

Functions

Basic device

Installation type

Floor standing wall model

Number of covers/doors

1

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_xEnergy_Basic_BP

Drawings

eaton-low-voltage-switch-gear-dimensions-1230dim-435.eps

mCAD model

bp_o_850_8_ep_w.dwg

bp_o_850_8_ep_w.stp

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Suitable for

Metrical mounting

Permissible load of the enclosure according to IEC 62208 - max

0 N

Permissible load of the door(s) according to IEC 62208 - max

0 N

Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890

0 W

Number of connector holes

0

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia