PRODUCT-DETAILS

E2.2N 800 Ekip G Hi-Touch LSIG 4p WMP

E2.2N 800 Ekip G Hi-Touch LSIG 4p WMP



General Information

Extended Product Type	E2.2N 800 Ekip G Hi-Touch LSIG 4p WMP
Product ID	1SDA072880R1
EAN	8015644767303
Catalog Description	E2.2N 800 Ekip G Hi-Touch LSIG 4p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2N 800 FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/G/HI-TOUCH-LSIG R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2361
Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 79.1 %

© 2024 ABB. All rights reserved.

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	272717f7-c6f0-4ac4-b16d-3553548f8aeb Italy (IT)
Simplified SCIP	9a5c0c87-3d90-4059-a59b-489901b36edc Germany (DE) d83baee8-6f13-4755-9764-93a1ef5c9fa5 Estonia (EE) 9558b63e-f1be-4c40-8c09-676aa149ec09 Greece (GR) a1fd3b09-fd67-47b7-a199-9baa422fcf6a Sweden (SE) 9d528207-c4d7-4322-b187-4e2d8d101706 Germany (DE) 6f2b9c9e-8747-4715-81e6-08379da4b9a4 Belgium (BE) 1e630642-44d4-47ba-8b50-71dcd3b6663c Bulgaria (BG) cceb039f-87f1-446d-a3fb-38491b809511 Sweden (SE) bd6493c1-5e38-4778-84b5-b58751c8387c Portugal (PT) c51e14b6-9eb1-4050-8173-d5009f02a853 Denmark (DK) 1481da1e-6bb9-452c-a1fb-c1f7638b83dd Germany (DE) 8fe2e787-9133-48d1-a7fd-e44e9037bdf0 Germany (DE) 59e5fcb2-f561-417b-9ba0-69af98bce79f Finland (FI) ad866790-f1dd-4e04-8179-34f8c1a63725 Netherlands (NL) b1634e51-b6f6-4528-823d-37b9baf9d7e6 Poland (PL) 80df33f1-89cb-4231-a91d-c407f531ab58 Norway (NO) 327e0465-1b25-4c4d-847d-0c06ffd6a098 Hungary (HU) 5a027db6-5713-4ae9-ba2a-a886c9d11a0b France (FR) f9a8d308-e075-4441-b448-57da27f5816a Croatia (HR) 1e0dcd88-c6a1-4a30-b2c6-2351acb6042e Germany (DE) 6c57f2b4-f8dc-4595-871b-cca47220a606 Poland (PL) 1113e6cb-9030-454c-b4e7-14117f6ae058 Czech Republic (CZ) 074a2192-d6a6-4a0a-93b5-2921004a40c0 Poland (PL) 03707169-04eb-422f-b21c-1669cf02006d Hungary (HU) b0b96469-c095-4232-a2a5-872f0c5464b0 Spain (ES) f960b41e-1063-4d6f-b1a9-d3dd946c4ace France (FR) 94c61e95-578f-4f7f-a31f-4694e20f26dc Belgium (BE)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	ZBNPEFAQ200A000000XX
EAN	8015644767303
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	407 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	55 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm

© 2024 ABB. All rights reserved.

Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	60 kg
Package Level 1 EAN	8015644767303

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4P
Power Loss	72 W
Rated Current (I_n)	800 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I_u)	800 A
Rated Voltage (U_r)	690 V
Release	Ekip G Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E2.2
Suitable for IT Networks	Yes, 690V

© 2024 ABB. All rights reserved.

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.