Butoject® 897 +



Application

- printing industry
- laboratories
- manufacturing of paints and varnishes
- chemical industry
- metal and plastics processing
- recycling and waste disposal
- cleaning and maintenance
- fire brigades and forces

Qualities and advantages

- very good protection against extremely aggressive chemicals
- excellent wearing comfort
- very good temperature flexibility
- good mechanical resistance
- high tightness against gas

Article no. **Name**	**897 +** Butoject® 897 +
Material	butyl
Description	rolled edge roughened, powdered
Length (mm) **Total thickness (mm)**	350-370 0,47 ± 0,05
Colour **Size**	black 7, 8, 9, 10, 11
Classification	category III EN388:2016 2000X; EN374-1/Type A BCIAKL; EN 374-5 Virus





Features

- AQL ‹ 0,65
- ANTISTATIC fulfills the requirements of the draft standard for EN 16350:2014-07 for protective gloves against electrostatic hazards: volume resistance ‹ 1 x 10⁸ Ω; test atmosphere: air temperature (23 ± 1)° C, relative humidity (25 ± 5) %; tested by the KCL laborator
- excellent low degradation
- good grip by distinct roughened surface
- offers protection even when sensitivity is needed

www.kcl.de
sales@kcl.de

KCL GmbH
Industriepark Rhoen
Am Kreuzacker 9
36124 Eichenzell
Germany
Phone +49 6659 87-300
Fax +49 6659 87-318

by Honeywell

V071118 GB

Honeywell