Technical Specifications

TELESCOPIC POLE & ACCESSORIES

Description:

This telescopic pole , new generation, is ideal for the settlement of vertical temporary life lines. Light and compact (1.40 m retracted length), its innovative conception: can be easily extended by one person, in vertical or horizontal position. Over above, it can be easily transportable in a van or pickup because of its weak clutter and can be used in different domains (telecommunication, electricity…).
A complete range of connectors and accessories is available for the complete the poles.

References: 1006629



Features:

Raw Material: Vinylester resin
Sizes

Extended length: 6,05 M

Retracted length 1,55 M

Diameter : Ø 51 mm

Dielectric strength : 28 Kv to 30 Kv

Elements : 5

Weight : 3 kg

Nozzle : Universel

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

ANCHORAGE POINTS



1002977 Jiraf anchorage Sling



1002899 Connector Crochevit Jiraf : 150 mm

1003345 Jiraf adaptater



1002981 GO 100 Jiraf connector



1002900 Jiraf Super Rapidex Hook





Mechanism of locking by control lever



1006629	Telescopic pole Jiraf 6,5 M	5 elements vinyl ester telescopic pole with universal adapter (length 6.5 mtrs).
1002979	Jiraf telescopic pole	Same as the ref 1006629 in 9,38 M
1002899	Crochevit Jiraf	Wide opening aluminium connector (150mm opening).
1003345	Jiraf adaptater	Jiraf direction adaptater , compatible with an universal adaptater
1002977	Jiraf anchorage Sling	Galvanized cable sling with protection sheath : 1,5 M LENGHT
1002981	Jiraf GO 100 Hook	Light alloy connector with self locking gate and rope latch (100mm opening)
1002900	Jiraf Super Rapidex hook	Automatic snap hook in aluminium . Opening of 63 mm

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com