SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES

TO 20 (4) A 250 V AC

double-pole 	Changeover switch (DPDT)	1834.3311	1834.3312	1834.1102	1834.3302	1834.3309	1834.3603	1834.6103	Changeover switch with OFF position in the center (DPDT - Center OFF)	1839.3512	1839.1402	1839.1407	1839.1410	1839.1502	1839.1507	1839.1509	1839.1518
Lighting voltage in V																	
Actuator color / printing																	
Housing color																	
20 (4) A 250 V AC 1E4																	
20 (4) A 250 V AC																	
16 (4) A 250 V AC 1E4		●	●							●							
10 (8) A 400 V AC 5E4																	
10 (8) A 250 V AC 5E4																	
10 (4) A 250 V AC 1E4				●	●	●	●	●									
10 A 12 V DC																	
6 (4) A 250 V AC 5E4				●	●	●	●	●									
6 (4) A 250 V AC 1E4											●	●	●	●	●	●	●
6 (4) A 250 V AC																	
4 (2) A 250 V AC 1E4																	
30 mA 12 V DC																	
16 A 250 V AC 1 HP																	
16 A 125 V AC 1 HP																	
16 A 250 V AC 1/2 HP		●	●							●							
16 A 125 V AC 1/3 HP										●							
16 A 125 V AC 1/4 HP		●	●														
6 A 250 V AC 1/2 HP				●	●	●	●	●									
6 A 125 V AC 1/4 HP				●	●	●	●	●									
6 A 125 - 250 V AC 1/8 HP											●	●	●	●	●	●	●
6 A 125 V AC 1/10 HP																	
4 A 250 V AC 1/10 HP																	
Terminal type																	
Terminal description		6.3	6.3	4.8	6.3	6.3	6.3	4.8		6.3	4.8	4.8	4.8	4.8	4.8	4.8	4.8
Contact distance in mm		≥ 3	≥ 3	≥ 3	≥ 3	≥ 3	≥ 3	≥ 3		≥ 3	≥ 3	≥ 3	≥ 3	≥ 3	≥ 3	≥ 3	≥ 3
Contact material		Ag	Ag	Ag	Ag	Ag	Ag	Ag		Ag	Ag	Ag	Ag	Ag	Ag	Ag	Ag
EN 60335 cap. 30 conform “G”							●										
Miscellaneous							cover frame 33.2 long	lower lying flange			momentary function both sides	momentary function both sides	dust protection inlay momentary function both sides				dust protection inlay
Stock version					●						●	●			●		