Cut protection

KRYTECH 574

Cut protection, comfort and enhanced grip and oil proofness with Grip & Proof technology.



GRIP & PROOF TECHNOLOGY

CUT PROTECTION
LEVEL C

EN388	EN407	ANSI CUT
4X31C	X1XXXX	A3 CUT

ANSI		CATEGORY 3
6	GR	CE
ABRASION	ISO 18889	0334

DEXTERITY

EN ISO 21420: 5/5

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

SPECIFIC ADVANTAGES

Durability
- Excellent abrasion resistance due to the nitrile coating

Productivity
- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection
- Oilproof, repels oil penetration and reduce dermatitis

Care for the environment
- Recycled material in the packaging: 30 %

INDUSTRIES
- Automotive/mechanical industry
- Mechanical industry
- Aeronautics industry

APPLICATIONS
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Precision assembly
- Machine maintenance
- Maintenance in wet environments
- Assembly of small oily parts
- Automotive assembly
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Machining parts using cutting oil

Edit 27/06/2025

Cut protection

KRYTECH 574

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	X	3	1	C	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread



ISO 18889 — PROTECTION AGAINST PESTICIDES

GR: Re-entry tasks

ANSI CUT — CUT RESISTANCE



A3 ≥ 1000 G

FOOD CONTACT

US (FDA)

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibers
Gauge	21
Exterior finish	Fully-coated
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Blue
European sizes	6 7 8 9 10 11

LOGISTIC DETAILS

Packaging	12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/11/24/2729
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 27/06/2025