

ABAS 18-63 AS Set 2 x 8 Ah

Cordless band saw for cutting depths of up to 63.5 mm

Ergonomic and compact band saw for conveniently cutting various materials and mobile applications. Including battery starter set of 2 x 8 Ah ProCORE batteries and rapid charger.

Product number: 7 135 01 62 00 0

Details

- Compact size and convenient two-handed operation for safe and low-fatigue working.
- More options – there are no limits on the flexible machining of a huge range of materials (e.g. steel, aluminium and plastic) thanks to rapid saw blade changes without the need for tools.
- Precise sawing results thanks to low-vibration saw blade motion and LED light on the working area.
- No troublesome adjustment of the saw blade after blade changes.
- Pleasant working with a soft grip.
- Vibration-free saw blade motion.
- Safety On/Off switch.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. “Electronic Cell Protection” (ECP) protects the battery from overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- 1 x BIM 733T14 MS band saw blade
- 2 ProCORE 18 V 8.0 Ah battery pack
- 1 x GAL18 V-160 AS rapid charger
- 1 plastic tool case (L-BOXX 238)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Speed, no load	162 rpm
Width	200 mm
Height	255 mm
Length	355 mm
Max. cutting depth	63.5 mm
Dimensions of saw blade	733 x 13 x 0.35 mm
Weight without storage battery	3.30 kg

Sound pressure level LpA Uncertainty of measured value KpA	79 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	90 dB 3 dB
Uncertainty of measured value KpCpeak Vibration value 1 αhv 3-way	3 dB 5,3 m/s²
Uncertainty of measured value Kα	1,5 m/s²

Application examples







