Date: 23/01/2024

F73.100/1, 0...120°C, L1=240 mmx8mm,

Gas actuated thermometer, stainless steel series

Item number:	3908402
Quantity:	1 pcs.
Order code:	F73.100-C1F-1BK-C0240-N03-4-HZZ-ZZZZZZ G7 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/1, 0...120°C, L1=240 mmx8mm, plain, without thread radial bottom Surface mounting bracket, die cast aluminium standard capillary stainless steel 1.4571 Capillary length: 3 m laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: 0 °C ... 120 °C Connection design: 1, plain stem Process connection: plain, without thread Stem diameter: 8 mm Insertion length L1: 240 mm Capillary: standard capillary stainless steel 1.4571 Capillary length: 3 m Design of case mounting: Surface mounting bracket, die cast aluminium Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2024 - WIKA Instruments s.a.r.l.