Specifications

Eaton 102715



Catalog Number: 102715

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 1 pole, 175A, 10 output terminals

General specifications

Product Name
Eaton xEnergy Basic LV systems Low voltage switchgear

Catalog Number
102715

EAN
4015081025756

Product Length/Depth
43 mm

Product Height
71 mm

Product Width
45 mm

Product Weight
0.23 kg

Compliances
RoHS conform

Certifications
IEC 60 947 -7 -1
UL 1059

Powering Business Worldwide

Product specifications

Special features

Clicks on DIN-rail or on base plate.
Save time on wiring.
Save 80% on space used.
Modular construction, 1-4 pole Systems can be built with several blocks.
Material, hexagon socket set screw: Steel
Zinc plated (Hexagon socket set screw, Surface finish)

Functions

Additional equipment

Torque rating

6 Nm - 10 Nm / 53.1 lbf - 88.5 lbf (incoming). 3 Nm - 4 Nm / 26.5 lbf - 35.4 lbf (outgoing)

Conductor cross section (flexible, fine-strand) with cable end sleeve - max

70 mm²

Conductor cross section (flexible, fine-strand) with cable end sleeve - min

2.5 mm²

Conductor cross section (solid, solid-strand) - max

70 mm²

Conductor cross section (solid, solid-strand) - min

2.5 mm²

Amperage rating

175 A

Rated short-time withstand current (Icw)

11 kA

Voltage rating at DC Cu (IEC) - max

1500 VDC

Number of poles

Single-pole

Degree of protection

IP20

Mounting position

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_BPZ-KB

Drawings

eaton-dimensions-mas-bpz-kb-10-175.eps

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Universal

Clamp material

Plain

Brass

Comparative tracking index (CTI)

600 V

Housing material

PA66

Housing color

Light gray (RAL 7035)

Mounting method

Flush mounting

Floor standing distribution board

Surface mounting

Flame classification (UL 94)

V-0

Heat deflection temperature

100 °C

Number of clamp positions per pole

11

Number of clamping units per pole

11

Rated peak withstand current

30 kA

Voltage rating at AC Cu (CSA) - max

600 VAC

Voltage rating at AC Cu (IEC) - max

1000 VAC

Voltage rating at AC Cu (UL) - max

600 VAC

Rated operation current (Ie) Cu (CSA)

175 A

Rated operation current (Ie) Cu (IEC)

175 A

Rated operation current (Ie) Cu (UL)

175 A

Terminal capacity (single/multi-wire)

2.5 mm² - 10 mm² (outgoing, fine wire (with sleeve))

6 - 2/0 AWG (incoming)

14 - 6 AWG (outgoing)

14 - 8 AWG (outgoing, fine wire (with sleeve))

2.5 mm² - 16 mm² (outgoing)

16 mm² - 70 mm² (incoming)

6 - 1 AWG (incoming, fine wire (with sleeve))

16 mm² - 50 mm² (incoming, fine wire (with sleeve))

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia