Technical Data Sheet

T-Rex Super Glue Tape

286853 – 19mm x 4.5m 6/cs



Properties

- A specialty, high performance, double coated tape
- The acrylic adhesive has exceptional tack and peel strength to provide a strong, permanent bond
- The thick adhesive layer makes bonding to rough or uneven surfaces easy
- Excellent for bonding, mounting or laminating to various materials and surfaces

Highlights

- High performance acrylic adhesive system
- Bonds to a multitude of materials
- High tack adhesive provides a quick, strong bond
- Polyester carrier film adds dimensional stability
- Thick adhesive layer aids bonding to rough surfaces

Technical Data

Adhesive Thickness Each Side:	.0035” (.089mm)
Film Thickness:	.0005” (.0127mm)
Total Thickness (without liner):	.0075” (.191mm)
Liner (55# Kraft):	.0032” (.081mm)
Peel Adhesion (each side): 20 Min. Dwell (PSTC-101)	150 oz./inch
Loop Tack (Each side) (PSTC 16):	100 oz./inch
Holding Power (PSTC-107): 1” x 1” x 1000g	24+ hours

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual rolls may vary slightly from these averages.
The user should determine whether a product is fit for a particular purpose and is suitable for the user’s method of application before use.