Date: 11/04/2023

TR10-B, 1xPt100, 3-w, Cl.B, -50/250°C (F), Ø 6 mm, terminal block

TR10-B RTD assembly for additional thermowell

Item number:	48727993
Quantity:	1 pcs.
Order code:	TR10-B-ZZZZ-13DR-BS1A-ZZ-ASBR-150-0600-60R-Z-ZZ R1B 0775Z0-KA-Z-WIKA0ZS
Overview:	TR10-B, 1xPt100, 3-w, Cl.B, -50/250°C (F), Ø 6 mm, terminal block Diameter measuring insert: Ø 6 mm, 1.4571, l1/A/U2=600 mm Head / housing: BS (Alu), Strd.-gland, M20x1.5, terminal block Neck tube: 12x1.5 mm, 1.4571, M24 x 1,5 - G 1/2 B, MH=150 mm (approx. 6 inch) Sealing: Copper Specifications according to data sheet: TE 60.02 Measuring insert length (spare) [l5]: 775 mm
Details:	TR10-B RTD assembly for additional thermowell Specifications according to data sheet: TE 60.02 1xPt100, 3-wire Class B, IEC 60751 Temperature range of selected class: -50...+250°C Head / housing: BS, Aluminum, flat cover Cable entry: Standard cable entry Thread size cable entry: M20 x 1.5 Transmitter: Without (terminal block) Connection to neck tube: M24 x 1,5 Neck tube: D = 12 x 1.5 mm (DIN 43772) Thread size: G 1/2 B Neck tube material: Stainless steel 1.4571 Neck length [MH/N]: 150 mm (approx. 6 inch) Insertion length [A] [l1/A/U2]: 600 mm Diameter measuring insert: 6 mm Sheath material measuring insert: Stainless steel 1.4571 Sealing: Copper Measuring insert length (spare) [l5]: 775 mm

© 2023 - WIKA Instruments s.a.r.l.