Specifications

Eaton 116288

Catalog Number: 116288

Eaton xEnergy Basic LV systems Low voltage switchgear. Cable interconnect frame IP54, HxWxD=200x600x320mm



General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic base element	116288
EAN	**Product Length/Depth**
4015081160273	325 mm
Product Height	**Product Width**
205 mm	605 mm
Product Weight	**Compliances**
7.84 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory
Accessory consideration
Service distribution board IVS
Floor-standing enclosure

Special features

For total weight >; 300 kg
Cladding removable on all sides
Can be fitted to top or bottom of the enclosure
Supplied assembled
Including fixing sundries
Cable clamp rail not included as standard

Type

Additional equipment for floor-standing service distribution board IVS

Accessory/spare part type

Cable marshalling box

Surface finishing

With powder coating

Color

Gray

Degree of protection

IP54

Unit type

Modular system

Load capacity - max

350 kg

RAL-number

7035

Suitable for enclosure building length/depth

320 mm

Suitable for enclosure building width

600 mm

Suitable for length/depth

320 mm

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Suitable for width

600 mm

Material

Steel

Sheet steel

Housing material

Sheet steel

Model

Base complete

Mounting method

Floor standing distribution board

Suitable for

Cable patch

Functions

Additional equipment

Impact strength

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia