Specifications

Eaton 289971

Catalog Number: 289971

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 250 A/63 A



General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic other accessory	289971
EAN	**Product Length/Depth**
4015082899714	51 mm
Product Height	**Product Width**
84 mm	427 mm
Product Weight	**Compliances**
1.3 kg	RoHS conform

Powering Business Worldwide

Product specifications

Fitted with:

N-rail

Functions

Additional equipment

Conductor cross section (flexible, fine-strand) with cable end sleeve - max

10 mm²

Conductor cross section (flexible, fine-strand) with cable end sleeve - min

1.5 mm²

Conductor cross section (solid, solid-strand) - max

0 mm²

Conductor cross section (solid, solid-strand) - min

0 mm²

Amperage rating

250 A

Number of poles

Four-pole

Degree of protection

IP20

Mounting position

Universal

Mounting method

Flush mounting

Surface mounting

Floor standing distribution board

Number of clamp positions per pole

12

Number of clamping units per pole

12

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_BPZ-KB

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia