Specifications

# Eaton EP-400198

## Catalog Number: EP-400198

Eaton Moeller series SLC Stack light compact, Green, Yellow, Red, 24 V AC/DC, Pulsed tone, Wall mounting

### General specifications

**Product Name**
Eaton Moeller® series SLC Signal tower compact

**Catalog Number**
EP-400198

**Model Code**
SLC-FW-RYG-AP-24UC

**EAN**
4015082954406

**Product Length/Depth**
79 mm

**Product Height**
237 mm

**Product Width**
61 mm

**Product Weight**
0.205 kg

**Certifications**
CE
IEC/EN 60947-5-1
IEC/EN 60529
UL Category Control No.: NKCR, NKCR7

UL File No.: E29184
UL report applies to both US and Canada

## Product specifications

### Type

Complete device

### Product Category

SL signal towers

### Fitted with:

Push-in

### Pollution degree

3

### Alarm type

Pulsed tone

### Connection to SmartWire-DT

No

### Mounting Method

Wall

### Illumination

Continuous LED
Red blinking LED

### Decibel

70 dB

### Ambient operating temperature - max

50 °C

### Ambient operating temperature - min

-25 °C

### Leakage current

0.003 A

### Outside diameter

61 mm

### Radiation angle

360 °

### Rated operational voltage (Ue) - max

24 V

### Rated operational voltage (Ue) - min

24 V

### Color

Black tube
Green

## Resources

### Brochures

SL4, SL7, SLC Stack light overview brochure BR047017

SLC Stack Light Compact Flyer sa047011

### Declarations of conformity

DA-DC-00004994.pdf

DA-DC-00004257.pdf

DA-DC-00004998.pdf

DA-DC-00004253.pdf

### Installation instructions

eaton-operating-devices-stacklight-compact-slc-instruction-leaflet-il047032zu.pdf

### mCAD model

eaton-slc-fw-ryg-3d-model.stp

eaton-slc_fw_ryg-drawing.dwg

Yellow

Red

### Lens color

Green

Yellow

Red

### Voltage type

AC

DC

### Material

UV Protected material

### Mounting position

As required

### Degree of protection

IP66

NEMA 4X

### Overvoltage category

III

### Lifespan, electrical

50,000 h

### Light type

Continuous light

Red blinking light

### Loudness

70 db

### Light modules

LED

### Number of modules

1

### Rated operational voltage

24V AC/DC +/-10% (50/60hz)

### Terminal capacity

Push-in 6-pole

up to 1,5mm² without plastic collar

up to 0,75mm² with plastic collar

### Voltage type of operating voltage

AC/DC

### Operating voltage at AC, 50 Hz - min

21.6 V

Operating voltage at AC, 50 Hz - max

26.4 V

Operating voltage at AC, 60 Hz - min

21.6 V

Operating voltage at AC, 60 Hz - max

26.4 V

Operating voltage at DC - min

21.6 V

Operating voltage at DC - max

26.4 V

Color light 1

Green

Color light 2

Yellow

Color light 3

Red

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia