# Daikin AC Domestic units to KNX Interface




**Item number: INKNXDAI001I000**

The Daikin-KNX interface allows full bidirectional communication between Daikin air conditioner domestic units and KNX installations. It connects directly to the indoor unit and delivers complete interoperability with KNX.

*Daikin to KNX - 1 indoor unit*

## Features and benefits

- **ETS configuration**
  The interface is configured using the ETS standard configuration tool software.
- **Multiple energy efficiency functions available**
  Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.
- **Total unit control and monitoring from KNX**
  Through internal variables, running hours counter (for maintenance purposes), and error indication.
- **AC unit control by both remote controller and KNX**
  The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.
- **Compatible with all KNX thermostats in the market**
  All the required DPT objects to be compatible with all KNX thermostats in the market are available.
- **Smooth KNX thermostat integration**
  KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.
- **Up to two scenes saved/executed from KNX**
  Up to two scenes can be saved and executed from KNX.
- **Compact dimensions, allowing inside installation**
  The interface can be quickly installed inside the AC unit thanks to its reduced dimensions.

# Daikin AC Domestic units to KNX Interface



## General

| | |
|---|---|
| **Net Width (mm)** | 71 |
| **Net Height (mm)** | 71 |
| **Net Depth (mm)** | 27 |
| **Net Weight (g)** | 80 |
| **Packed Width (mm)** | 12 |
| **Packed Height (mm)** | 7 |
| **Packed Depth (mm)** | 9 |
| **Packed Weight (g)** | 100 |
| **Operating Temperature °C Min** | -25 |
| **Operating Temperature °C Max** | 60 |
| **Storage Temperature °C Min** | -40 |
| **Storage Temperature °C Max** | 85 |
| **Power Consumption (W)** | 0.232 |
| **Input Voltage (V)** | 29 VDC |
| **Power Connector** | 2-pole |
| **Configuration** | ETS |
| **Capacity** | 1 Indoor unit. |
| **Installation Conditions** | This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit. |
| **AC Model Compatibility** | Daikin Residential |

# Daikin AC Domestic units to KNX Interface



## General

| | |
|---|---|
| **Content of Delivery** | Intesis Gateway, Installation Manual, AC Connection cable. |
| **Housing Materials** | Plastic |
| **Warranty (years)** | 3 years |
| **Packaging Material** | Cardboard |

## Identification and Status

| | |
|---|---|
| **Product ID** | INKNXDAI001I000 |
| **Country of Origin** | Spain |
| **HS Code** | 8517620000 |
| **Export Control Classification Number (ECCN)** | EAR99 |

## Physical Features

| | |
|---|---|
| **Connectors / Input / Output** | KNX, HVAC port. |
| **LED Indicators** | KNX |

## Certifications and Standards

| | |
|---|---|
| **ETIM Classification** | EC001604 |
| **WEEE Category** | IT and telecommunications equipment |

## Use Case




Integration example.