Date: 12/04/2023

RLS-1000; Guide tube length: 450 mm; 2 switching outputs

RLS-1000; Guide tube length: 450 mm; 2 switching outputs

Item number:	48794365
Quantity:	1 pcs.
Order code:	RLS-10004M103000104000ZZZZZZZZZZZZ1CZ8K045004ZC Z1W101ARS1ZL4
Overview:	RLS-1000; Guide tube length: 450 mm; 2 switching outputs Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 2 switching outputs Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 300 mm Switching function - Switch output 2 : Normally closed / n.c. Switch position - Switch output 2: 400.0 Electrical connection: Angular connector DIN 175301-803 A, IP65 pin assignment el. connection: see product label Process connection: G3/4, installation from outside Guide tube length: 450 mm mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 22 mm, 1.4571, PN16 Specifications according to data sheet: LM 50.03
Details:	RLS-1000; Guide tube length: 450 mm; 2 switching outputs Magnetic float switch, Stainless steel version Model RLS-1000 Output Signal: 2 switching outputs Unit of measure switching position: mm Switching function - Switch output 1 : Normally closed / n.c. Switch position - Switch output 1 : 300 mm Switching function - Switch output 2 : Normally closed / n.c. Switch position - Switch output 2: 400.0 Electrical connection: Angular connector DIN 175301-803 A, IP65 pin assignment el. connection: see product label Process connection: G3/4, installation from outside Guide tube length: 450 mm mm medium temperature: -30 °C ... 80 °C Wetted parts: Stainless steel 1.4571 Float: Cylindrical float Ø 22 mm, 1.4571, PN16 Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.