Specifications

Eaton 9701-5001-00P



Catalog Number: 9701-5001-00P

Eaton DG1 Variable frequency drive, 230 V AC, 3-phase, 170 A, 45 kW, IP21/NEMA1, DC link choke

General specifications

Product Name
Eaton DG1 variable frequency drive

Catalog Number
9701-5001-00P

EAN
4015081734139

Product Length/Depth
340.7 mm

Product Height
888.5 mm

Product Width
288 mm

Product Weight
68.3 kg

Certifications
CUL
Safety requirements: IEC/EN 61800-5
UL File No.: E134360
UL report applies to both US and Canada
IEC/EN61800-3
EAC
CE
C-Tick
Certified by UL for use in Canada
IEC/EN61800-5
UL
UkrSEPRO
UL Category Control No.: NMMS, NMMS7
IEC/EN 61800-3
RoHS, ISO 9001
CSA-C22.2 No. 274-13
Specification for general requirements: IEC/EN 61800-2
UL508

Powering Business Worldwide

Features & Functions

Features

Externally accessible fan

Temperature-controlled fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

General

Air volume capacity

395 m³/h

Cable length

C3 ≤ 50 m, Radio interference level, maximum motor cable length

200 m, screened, maximum permissible, Motor feeder

C2 ≤ 10 m, Radio interference level, maximum motor cable length

Degree of protection

NEMA 1

IP21

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Fitted with:

IGBT inverter

DC link choke

Radio interference suppression filter

Internal DC link

Control unit

Additional PCB protection

PC connection

Multi-line graphic display

Frame size

FS5

Mounting position

Vertical

Number of slots

2 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact

(BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only

Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

Shock resistance

Storage and transportation: maximum 15 g, 11 ms (inside the packaging)
Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27
UPS drop test (for weights inside the UPS frame)

Suitable for

Branch circuits, (UL/CSA)

Vibration

Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6
Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude

Climatic environmental conditions

Altitude

Max. 2000 m for Corner Grounded TN Systems
Above 1000 m with 1 % derating per 100 m
Max. 1000 m
Max. 3000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-30 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Efficiency

97.7 % (η)

Heat dissipation at current/speed

1208 W at 100% current and 0% speed
1627 W at 50% current and 0% speed
1924 W at 100% current and 90% speed
469 W at 25% current and 0% speed
612 W at 25% current and 50% speed
638 W at 100% current and 50% speed
857 W at 50% current and 50% speed
975 W at 50% current and 90% speed

Input current ILN at 110% overload

189 A

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

154 A

Assigned motor current IM at 230 V, 50 Hz, 110% overload

173 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

141 A

Assigned motor current IM at 230 V, 60 Hz, 110% overload

192 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

60 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase, 110 % overload

75 HP

Input current ILN at 150% overload

157.3 A

Leakage current at ground IPE - max

5.4 mA

Mains current distortion

25 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

208 V

Mains voltage - max

240 V

Operating mode

Sensorless vector control (SLV)
Speed control with slip compensation
U/f control
Torque regulation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

230 V AC, 3-phase
240 V AC, 3-phase

Overload current IL at 110% overload

232.1 A

Overload current IL at 150% overload

255 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

211 A

Apparent power

Apparent power at 230 V

84.1 kVA

Apparent power at 240 V

87.7 kVA

Braking function

Braking resistance

1.4 Ω

Braking torque

Max. 30 % MN, Standard - Main circuit
Adjustable to 150 % (I/Ie), DC - Main circuit
Adjustable to 150 %, DC - Main circuit
Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Switch-on threshold for the braking transistor

425 VDC

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

Communication

Communication interface

Modbus RTU, built in

Rated operational current (Ie) at 150% overload

170 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

45 kW

Rated operational power at 220/230 V, 50 Hz, 3-phase, 110% overload

55 kW

Rated operational voltage

240 V AC, 3-phase

230 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

250 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

3.6 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

240 VAC

CANopen®, optional

SmartWire-DT, optional

Ethernet IP, built in

BACnet MS/TP, built in

DeviceNet, optional

Modbus TCP, built in

PROFIBUS, optional

Connection to SmartWire-DT

In conjunction with DXG-NET-SWD SmartWire DT module

Yes

Protocol

CAN

PROFINET IO

MODBUS

Other bus systems

DeviceNet

TCP/IP

PROFIBUS

BACnet

EtherNet/IP

Design verification

Equipment heat dissipation, current-dependent Pvid

1724 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

170 A

Static heat dissipation, non-current-dependent Pvs

19.32 W

Heat dissipation details

Operation (with 150 % overload), allow for derating

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Resources

Application notes

Torque control

Real time clock and use of the timers

Analog I/Os

Load balancing in multi motor applications

PID controller

Smoke Mode and fire mode

Operating at low temperatures

Motor data and V/f curves

Digital I/Os

Electromagnetic compatibility (EMC)

Dual Rating What exactly does that mean?

DG1 in pump and fan applications

Starting, stopping and operation

Connecting drives to generator supplies

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004861.pdf

DA-DC-00004676

Drawings

eaton-frequency-inverter-dg1-dimensions-005.eps

eaton-frequency-inverter-dg1-3d-drawing-005.eps

eCAD model

DA-CE-ETN.DG1-32170FN-C21C

Manuals and user guides

MN040002_EN

mCAD model

DA-CD-dg1_fs5

DA-CS-dg1_fs5

Multimedia

Power XL General Purpose Drives

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia