Date: 11/04/2023

R5502/4, NS100, 0...200°C, L1=160x8mm

Bimetal thermometer, stainless steel version

Item number: 48774637

Quantity: 1 pcs.

Order code: R5502 -4-C1L-ND-C160GZZ-AHAZZZZ TB FZZZESZSVID-AZ1ZZZZZ1ZZZZ

Overview:
R5502/4, NS100, 0...200°C, L1=160x8mm
Process connection: 1/2 NPT, radial bottom
flat instrument glass,
class 1 per EN 13190
Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
WIKA Serial number *...*

Details:
Bimetal thermometer, stainless steel version
Specifications according to data sheet: TM 55.01
Case: stainless steel
Stem material: stainless steel
Model: R 5502, nominal size 100, location of stem radial
Connection design: 4, compression fitting, sliding on stem
Unit: °C
Scale range: 0 °C ... 200 °C
Process connection: 1/2 NPT
Stem diameter: 8 mm
Insertion length L1: 160 mm
Window: flat instrument glass
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Case: Stainless steel
Connector location: radial bottom
Version: standard
Stem material: stainless steel
Permissible ambient temperature: -40 ... +70 °C
Manufacturer logo: *WIKA*
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
serial number on dial: Serial number *...*
Explosion protection: ATEX
Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.