Date: 11/04/2023

AL-ADF-RL2"-LU-L3,250/14-V52A

AL-ADF-RL2"-LU-L3,250/14-V52A

Item number: 48752475

Quantity: 1 pcs.

Order code: FLS-CBMDZ001011000BA2ZZGFZZ3200UZZZZZZZZZZZZZZZZZZ
FLRVIA32501NZZZZ

Overview:
AL-ADF-RL2"-LU-L3,250/14-V52A
Float Switch Type FLS-SAD
Approval: ATEX Ex d; TÜV 13 ATEX 7399 X II 2 G Ex db IIC T6 Gb, II 2 D Ex tb IIIC T80°C Db
Material: Stainless steel 316L (EN 1.4404)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Housing: Aluminium ATX
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Change-over (SPDT) 3200 mm
Switch rating: max. AC/DC 250V; 100VA/60W; 1.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 1 pc
Guide tube: OD 14 mm Insertion length (L): 3250 mm
Float stop: Float collar
Float fits through the connection nozzle
Weight: 2.2 kg
Brand name: Kubler France

Details:
AL-ADF-RL2"-LU-L3,250/14-V52A
Float Switch Type FLS-SAD
Approval: ATEX Ex d; TÜV 13 ATEX 7399 X II 2 G Ex db IIC T6 Gb, II 2 D Ex tb IIIC T80°C Db
Material: Stainless steel 316L (EN 1.4404)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Housing: Aluminium ATX
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Change-over (SPDT) 3200 mm
Switch rating: max. AC/DC 250V; 100VA/60W; 1.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 1 pc

© 2023 - WIKA Instruments s.a.r.l.

Guide tube: OD 14 mm Insertion length (L): 3250 mm
Float stop: Float collar
Float fits through the connection nozzle
Weight: 2.2 kg
Brand name: Kubler France

© 2023 - WIKA Instruments s.a.r.l.