PRODUCT-DETAILS

E2.2B 2000 Ekip Hi-Touch LSI 3p F HR

E2.2B 2000 Ekip Hi-Touch LSI 3p F HR



General Information

Extended Product Type	E2.2B 2000 Ekip Hi-Touch LSI 3p F HR
Product ID	1SDA071028R1
EAN	8015644748784
Catalog Description	E2.2B 2000 Ekip Hi-Touch LSI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2B 2000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSI R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy (IT)
Simplified SCIP	7f3be359-1216-4d35-b9d4-eab9cbb290fd Poland (PL) cc5cb3c7-f20f-4e57-a699-41c96b5a1eef Norway (NO) de6447a0-df24-4a20-8466-f5f11a930a19 Finland (FI) de9a0119-6bd3-4d97-a5d3-1e74d280ccf7 Belgium (BE) 8ad28a13-de77-4592-95fd-897a501569c8 Germany (DE) 8b03cfe9-7657-4778-acb1-5e456af5c76a Denmark (DK) 08ff7a7d-f7c4-4a97-ab1f-2f60e52ccc4e Germany (DE) 18044daa-d0c0-4608-bafb-451bb9d8efe4 Croatia (HR) 5ede7a36-3b83-4497-b7e0-ef217691ad89 Czech Republic (CZ) e5eed5bf-546a-4db4-a608-d4b83c43c056 Poland (PL) bf55e5c1-47fb-4603-bc85-150f2bba6810 Netherlands (NL) 13fc1439-00ad-45bf-abdd-5ede1ce20a7d Hungary (HU) 7635dc57-155c-4b3b-8d16-637f7a9317ca Estonia (EE) f49fce99-7561-4c32-880a-478431f7efd7 Greece (GR) 05702ea0-ab49-475f-8469-3cf48dabeb77 Portugal (PT) 8d8d3917-aca7-4875-98c5-244d35793f56 Bulgaria (BG) 64831dac-5718-413a-b2dd-c2a16236b94f Sweden (SE) 55ebef71-4502-4891-8767-e9a15ef09392 Poland (PL) a940f727-3880-42c1-bdc0-d5e1d498ddaf France (FR) 560d9c18-bf6e-4a6e-b95a-82f0dcbd0d2c Sweden (SE) f40ef067-0a7a-4928-831d-6affa0d2f0c7 Germany (DE) 6e3f01fd-be03-4be8-9d80-b02a9984a4e1 Germany (DE) 7e9377e0-b60f-471e-982f-360fb85b51c6 France (FR) 1c74a6dc-b960-484a-a4e4-4114d79c6a3d Hungary (HU) 1ac41cb5-8851-4d50-97e5-9a58e2df1d99 Spain (ES) 5b96a5ce-08d7-4ea3-9d9d-b2ed25c73f5d Belgium (BE) a16503c8-c993-4d7a-9277-704db1bb451b Germany (DE)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	Z2BTEKBJ200A000000XX
EAN	8015644748784
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	46 kg
Package Level 1 EAN	8015644748784

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0083

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 10000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	212 W
Rated Current (I_n)	2000 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 42 kA (230 V AC) 42 kA (380 V AC) 42 kA (400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 42 kA for 3 s 42 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 42 kA (415 V AC) 42 kA (440 V AC) 42 kA (500 V AC) 42 kA (525 V AC) 42 kA (690 V AC) 42 kA
Rated Uninterrupted Current (I_u)	2000 A
Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M12
Release	Ekip Hi-Touch LSI

© 2024 ABB. All rights reserved.

Release Type	EL
Short-Circuit Performance Level	B
Standards	IEC
Sub-type	E2.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001000R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.