DATASHEET - M22-R-SWD

Potentiometer, Classical, M22, 22.5 mm, Bezel: titanium

Part no. **M22-R-SWD**
179292

Product name	Eaton Moeller® series M22 Potentiometer
Part no.	M22-R-SWD
EAN	4015081743780
Product Length/Depth	48 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.019 kilogram
Certifications	CSA Class No.: 3211-07 CSA File No.: 2324643 UL IEC/EN 60947 UL File No.: E29184 UL Category Control No.: NKCR CSA
Product Tradename	M22
Product Type	Potentiometer
Product Sub Type	None
Bezel color	Titanium
Design	Classical
Electric connection type	Screw connection
Functions	For connecting to SmartWire-DT
Degree of protection	IP65 NEMA Other
Opening diameter	22.5 mm
Type	Potentiometer
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Power consumption	0 W
Resistance	0 Ohm
Connection to SmartWire-DT	Yes

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Potentiometer for command devices (EC001027)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Potentiometer for command devices (ecl@ss10.0.1-27-37-12-27 [AKF045014])

Resistance	Ohm	0
Power consumption	W	0
Hole diameter	mm	22.5
Number of revolutions		1 - 1

Type of electric connection			Screw connection
Degree of protection (IP)			IP65
Degree of protection (NEMA)			Other

© 04/2023 by Eaton Industries GmbH