Date: 11/04/2023

TW10-P PPW 3 mm 1/2 NPT female U=200 mm B=0.260 inch (6.6 mm) SS316/316L

Flanged Thermowell TW10, solid machined

Item number: 48788142

Quantity: 1 pcs.

Order code: TW10-P-A-M-CEBUD-N-0020000057G3G3DA02500220ZZ-ZZ 00250 Z00250ZZZZYQ1Z

Overview:
TW10-P PPW 3 mm 1/2 NPT female U=200 mm B=0.260 inch (6.6 mm) SS316/316L
Flange: 1 1/2 inch 300 lbs RF
Connection to thermometer [N]: 1/2 NPT female
Material: SS316/316L
Flange material: SS316/316L
Thermowell style: Tapered
Head length [H]: 57 mm
Insertion length [U]: 200 mm
Bar diameter [Bd or F2]: 30 mm
Root diameter [Q]: 25 mm
Tip diameter [V or F3]: 22 mm
Bore size [B or d1]: 0.260 inch (6.6 mm)
Bore depth / stem length (US) [A]: 250 mm
Specifications according to data sheet: TW 95.10

Details:
Flanged Thermowell TW10, solid machined
Specifications according to data sheet: TW 95.10
Welding options: Partial penetration (throat depth 3 mm minimum)
Thermowell style: Tapered
Unit of measure: Metric (mm)
Flange size: ASME 1 1/2 inch
Pressure rating: Class 300
Flange face: RF (Raised face)
Connection to thermometer [N]: 1/2 NPT female
Pipe sched. /Intern. nozzle dia.: WIKA (Standard Germany)
Insertion length [U]: 200 mm
Head length [H]: 57 mm
Flange material: Stainless steel 316/316L
Material: Stainless steel 316/316L
Bar diameter [Bd or F2]: 30 mm
Bore size [B or d1]: 0.260 inch (6.6 mm)
Root diameter [Q]: 25 mm
Tip diameter [V or F3]: 22 mm
Bore depth / stem length (US) [A]: 250 mm
Tip thickness [Tt]: 0.250 inch (6.4 mm)
Model: TW10

© 2023 - WIKA Instruments s.a.r.l.