Professional PRCD-S ADVANCED protective adapter cable IP 44 3 m H07RN-F 3G1.5

Protection mobile des personnes pour les chantiers et l'utilisation permanente en plein air.



PRCD-S ADVANCED | 5 YEARS MANUFACTURER GUARANTEE | DGUV-I 203-006 K2 | FI-SAFETY | SPECIAL ROBUST | ~1 kΩ | TEST | ! | IP 44

Product number	1160210
EAN	4007123670321

DESCRIPTION

- Reliable protection against faulty electrical installations and dangerous electrical accidents.
- Enables users to safely operate electrical appliances on sockets whose proper functioning they are not familiar with.
- Highly recommended for use on construction and assembly sites and promoted by BG Bau.
- Meets the requirements of DGUV Information 203-006 Section 5.4.1:
- PRCD according to VDE 0661.
- Rated differential current 30 mA.
- All-pole switching, including protective conductor.
- Undervoltage release.
- No automatic restart after voltage recovery.
- The protective device must not be able to be switched on if the protective conductor is interrupted or live.
- If voltage occurs on the protective conductor during operation or if the protective conductor is interrupted, the protective device must switch off.
- If external voltage occurs on the protective conductor, e.g. due to drilling into a line of another circuit, the protective device must not switch off the protective conductor.
- Additional safety enhancement:
- Improved testing for protective conductor interruption from approx. 1kΩ.
- Glove detection (device cannot be switched on with insulating gloves in the event of a fault).
- Comprehensive function test by checking the entire signal chain from protective conductor monitoring to the FI switch function.
- Oil-resistant rubber cable for continuous outdoor use.
- With rubber safety plug and rubber safety coupling with cover.

Professional PRCD-S ADVANCED protective adapter cable IP 44 3 m H07RN-F 3G1.5

Protection mobile des personnes pour les chantiers et l'utilisation permanente en plein air.



Product number	1160210
EAN	4007123670321

TECHNICAL DATA

Cable quality	Rubber-Neoprene	**Connection**	Rubber plug/Earthed coupling
Cable length	3 m	**Plug system plug**	Type E and F (Protective contact with earth hole)
Cable designation	H07RN-F 3G1,5	**Plug system socket/ coupling**	Type F (Protective contact)
Cable colour	black	**Degree of protection (IP)**	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	**Weight of product (including packaging)**	1.07 kg
Weight of product (without packaging)	0.96 kg	**Dimension LxWxH (incl. packing)**	28.5 cm x 16.5 cm x 6.5 cm
Dimension LxWxH (without packing)	28 cm x 16.5 cm x 6 cm		

SCOPE OF DELIVERY

Professional PRCD-S ADVANCED protective adapter cable IP44 3m H07RN-F3G1.5