Date: 11/04/2023

LF-1; 0...16 mH2O gauge; 4 … 20 mA (pressure), 2-wire

Submersible pressure sensor for superior applications

Item number:	48788460
Quantity:	1 pcs.
Order code:	LF-1ZZZZZ-YG316-2DA-AM0070Z2BZZ-ZZZZZZ-Z W101ALF1Z-AA18MPZZLF
Overview:	LF-1; 0...16 mH2O gauge; 4 … 20 mA (pressure), 2-wire @ DC 8...36 V; 1.0% of span;-10...+50°C; 70 meter PUR ;1.4404 / 316L ; 4...20 mA-Standard(press): U+ brown, U- blue; Shield-grey Test protocol: with test protocol Specifications according to data sheet: LM 40.04
Details:	Submersible pressure sensor for superior applications

Specifications according to data sheet: LM 40.04
Measuring range: 0...16 mH2O gauge
Output signal: 4 … 20 mA (pressure), 2-wire
Power supply: DC 8...36 V
Accuracy: 1.0% of span
Cable material: PUR
Unit cable length: meter
Cable length: 70
Case material: 1.4404 / 316L
Permissible medium temperature: -10...+50°C
Test protocol: with test protocol
Pin assignment: 4...20 mA-Standard(press): U+ brown, U- blue; Shield-grey
shield: connected
Customer logo: WIKA standard
Customer address: WIKA Alexander Wiegand SE & Co. KG 63911 Klingenberg
Model name customer-specific: LF-1

© 2023 - WIKA Instruments s.a.r.l.