Specifications

Eaton 3-5002-008A

Catalog Number: 3-5002-008A

Eaton DM1 Variable frequency drive, 230 V AC, 3-phase, 7.8 A, 1.5 kW, IP20/NEMA0, 7-digital display assembly, Setpoint potentiometer, Brake chopper, FS1



General specifications

Product Name
Eaton DM1 Variable frequency drive

Catalog Number
3-5002-008A

EAN
4015081980734

Product Length/Depth
180 mm

Product Height
152 mm

Product Width
72 mm

Product Weight
1.2 kg

Certifications
C-Tick
CSA-C22.2 No. 274-17
IEC/EN61800-5
UL File No.: E134360
EAC
UL
UkrSEPRO
IEC/EN 61800-3
UL Category Control No.: NMMS, NMMS7
UL Listed
IEC/EN61800-3
CUL
CE
IEC/EN 61800-2
IEC/EN 61800-5-1
CSA-C22.2 No. 274-13
UL report applies to both US and Canada
CE marking
Certified by UL for use in Canada

Powering Business Worldwide

General

Air volume capacity

26 m³/h

Communication interface

BACnet TCP
DeviceNet, optional
Modbus RTU, built in
BACnet MS/TP, built in
CANopen®, optional
SmartWire-DT, optional
Modbus TCP, built in
Ethernet IP, built in
PROFIBUS, optional

Connection to SmartWire-DT

In conjunction with DXG-NET-SWD SmartWire DT module
Yes

Degree of protection

IP20
NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Features

Parameterization: Fieldbus
Parameterization: Keypad
Parameterization: Power Xpert inControl
Temperature-controlled fan

Fitted with:

Setpoint potentiometer
Brake chopper
IGBT inverter
7-digital display assembly
Internal DC link
Breaking resistance
Control unit
PC connection

Frame size

FS1

Mounting position

Vertical

Climatic environmental conditions

Altitude

Max. 3000 m
Above 1000 m with 1 % derating per 100 m
Max. 1000 m
Max. 2000 m for Corner Grounded TN Systems

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Heat dissipation at current/speed

112 W at 100% current and 90% speed
40 W at 25% current and 0% speed
47 W at 100% current and 50% speed
48 W at 25% current and 50% speed
58 W at 50% current and 50% speed
69 W at 50% current and 90% speed
71 W at 100% current and 0% speed
92 W at 50% current and 0% speed

Input current ILN at 110% overload

13.2 A

Input current ILN at 150% overload

9.4 A

Mains current distortion

40 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Number of slots

1 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Safety function/level

STO (Safe Torque Off, SIL2, PLc Cat 2)

Shock resistance

0.75 mm (peak) at 10 - 57 Hz, max. 1 g at 57 - 150 Hz, according to EN 61800-5-1, EN 60068-2-6: 10 - 150 Hz

Suitable for

Branch circuits, (UL/CSA)

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

Torque regulation
Sensorless vector control (SLV)
PM motors
U/f control
Speed control with slip compensation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

240 V AC, 3-phase
230 V AC, 3-phase

Overload current IL at 110% overload

12.1 A

Overload current IL at 150% overload

11.7 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

11 A

Rated operational current (Ie) at 150% overload

7.8 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

1.5 kW

Rated operational power at 220/230 V, 50 Hz, 3-phase, 110% overload

2.2 kW

Rated operational voltage

240 V AC, 3-phase

230 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

16 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

4 kHz, 1 - 16 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

240 V

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

6.8 A

Assigned motor current IM at 230 V, 50 Hz, 110% overload

8.7 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

6.3 A

Assigned motor current IM at 230 V, 60 Hz, 110% overload

9.6 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

2 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase, 110 % overload

3 HP

Braking function

Braking resistance

36 Ω

Braking torque

Adjustable to 150 %, DC - Main circuit

Max. 30 % MN, Standard - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Control circuit

Number of inputs (analog)

1

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of relay outputs

2 (parameterizable, 1 changeover contact and 1 N/O, 3 A (240 V AC) / 3 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 100 mA options incl.)

Design verification

Equipment heat dissipation, current-dependent Pvid

99 W

Rated operational current for specified heat dissipation (In)

11 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Resources

Application notes

Dual Rating What exactly does that mean?

Electromagnetic compatibility (EMC)

Connecting drives to generator supplies

Brochures

eaton-powerxl-dm1-variable-frequency-drives-brochure-br040016en-en-us.pdf

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004864.pdf

DA-DC-00004643.pdf

Installation instructions

DM1 IL PUB 53-675 TBG Change Request 12-24-21 Final (300 DPI).pdf

Installation videos

PowerXL Variable Frequency Drive DM1

Manuals and user guides

MN040049EN

MN040060EN

mCAD model

fs1-89-1309.stp

fs1_89_1309.dwg

Multimedia

PowerXL DM1 Variable Frequency Drive - Setup via Software

PowerXL DM1 Variable Frequency Drive - Setup via WebUI

PowerXL DM1 Variable Frequency Drive - PowerXpert inControl with Bluetooth

PowerXL DM1 Variable Frequency Drive - Establishing a Modbus TCP connection with software Power Xper

PowerXL DM1 Variable Frequency Drive - Configuration with keypad

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Sales notes

eaton-powerxl-dm1-variable-frequency-drives-flyer-fl040006en-en-us.pdf

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia