DATASHEET - DX-LN1-032

Main choke, Single-phase, 260 V + 0% (50/60 Hz), V AC, 32 A, 0.92 mH

Part no. DX-LN1-032
169791

General specifications	
Product name	Eaton DX Mains choke
Part no.	DX-LN1-032
EAN	4015081662869
Product Length/Depth	130 millimetre
Product height	140 millimetre
Product width	160 millimetre
Product weight	3 kilogram
Certifications	UL IEC/EN 61558-2-20-2000 CSA VDE 0570 Part 2-20/2001-04
Product Tradename	DX
Product Type	Accessory
Product Sub Type	Mains choke
Features & Functions	
Fitted with:	Terminations PE stud
Number of phases	1
Number of poles	Single-pole
General information	
Bore diameter	0 mm
Degree of protection	NEMA Other IP20
Duty factor	100 %
Insulation class	B
Product Category	Accessories
Suitable as	Net reactance coil
Switching frequency	3 kHz
Used with	DM1 DC1
Ambient conditions, mechanical	
Mounting position	Free surrounding areas > 50 mm Suspended horizontally Standing vertically
Shock resistance	3 shocks Shock duration: 11 ms
Vibration resistance	10 - 55 Hz, 0.35 mm 0 - 150 Hz, 1 g
Climatic environmental conditions	
Altitude	Max. 5000 m with current reduction Max. 1000 m
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-25 °C
Ambient storage temperature - max	85 °C
Ambient storage temperature - min	-25 °C
Operating temperature details	-25 - 40 °C (up to 70 °C with current derating)
Terminal capacities	
Terminal capacity	4 mm^2 20 - 10 AWG
Tightening torque	0.8 Nm, Screw terminals
Electrical rating	
Permissible connection voltage	Max. 260 V AC (50/60 Hz)

Rated current (Ith) at rated voltage DC - max		0 A
Rated frequency - min		50 Hz
Rated frequency - max		60 Hz
Rated inductance		0.92 mH
Rated operational current (Ie) - min		32 A
Rated operational current (Ie) - max		32 A
Rated operational voltage (Ue) - max		260 V
Relative short-circuit voltage		0 %
Voltage sag Uk		4 %

Design verification

Heat dissipation capacity Pdiss		0 W
Rated operational current for specified heat dissipation (In)		32 A
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Coil for low-voltage (EC002563)

Electric engineering, automation, process control engineering / Electronic coil and filter / Electronic choke coil / Electronic choke coil (unspecified) (ecl@ss13-27-42-01-90 [ADJ199012])

Suitable as interference suppression reactance coil		No
Suitable as net reactance coil		Yes
Suitable as commutation reactance coil		No
Suitable as ripple filter choke		No
Suitable as output reactance coil		No
Number of poles, primary side		1
Rated clock frequency	kHz	3
Rated operating frequency	Hz	50 - 60
Max. rated operation voltage Ue	V	260
Rated current AC	A	32 - 32
Max. rated current (Ith) at rated voltage DC	A	0
Rated inductance	mH	0.92
Degree of protection (IP)		IP20
Relative short circuit voltage	%	0
Resonance frequency	Hz	0
Degree of protection (NEMA)		Other

© 04/2023 by Eaton Industries GmbH