TECHNICAL SPECIFICATION

EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented

White / AKS270-000-100



DESCRIPTION

JSP's EVO®5 DualSwitch™ is fully certified to both EN 397 and EN 12492, with the ability to change between the two standards easily at the flick of a switch.

JSP have delivered an innovative helmet which can be used at ground level (EN 397) or at height (EN 12492).

OPTIONS

Black (AKS270-001-100)
Blue (AKS270-000-500)
Orange (AKS270-000-800)
Red (AKS270-000-600)
White (AKS270-000-100)

SAFETY STANDARDS

EN 397 • EN 50365 • EN 12492 • ANSI/ISEA Z89.1

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Micro

Side Impact Resistance
25 Joules

Lateral Deformation
Yes

Maximum Temperature
+50˚C

ABS Shell
Yes

Recyclable
Shell

Depth Adjustment
3D Harness

Universal Accessories Slot
Yes

Reflective Option
Optional

ID card holder
Optional

Fitted 4 point DualSwitch chinstrap (EN12492 and EN397 compliant)
Fitted

Product Weight
450g

Impact Resistance
100 Joules

EN 50365 ELECTRICAL INSULATION
1000V

Molten Metal
Yes

Minimum Temperature
-40˚C

EPP Liner
Yes

Textile
Harness

Wheel Ratchet
Yes

Ventilation
Yes

Integrated Eyewear
No

BSI Kitemark
Yes

JSPCheck
Yes

Size
53-64cm

FEATURES



Switch Down

The chinstrap release force of EN 12492 is greater than 500 Newtons. This limits the risk of losing the helmet during a fall.



EPP Liner

Our robust Expanded Polypropylene (EPP) liner ensures class leading impact attenuation, offering side, front and rear impact protection, as required in EN12492.



CR2

CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. A high intensity reflective material offering, on average, 60% more reflectivity than standard reflective clothing. CR2 is optional.



Switch Up

The chinstrap release force of EN 397 is between 150 and 250 Newtons. This limits the risk of choking, the chinstrap has been designed to release if snagged.



Secure fit

Featuring a fully adjustable 4-point chinstrap, easy to use Revolution® wheel ratchet and a 3D Adjustment harness, which offers 1-2-3 point depth settings for a perfect fit.



Accessories

Universal attachment slots enable fitting of Surefit™ safety visors and Sonis® ear defenders. EVOSpec® integrated eyewear. Lamp bracket & business card holder. The Visilite® helmet wearer illumination system can also be fitted to increase low light visibility.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





Electrical Protection to 1000V

Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield, an internationally recognised symbol of quality.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Ventilation

The shell and EPP liner are vented to increase comfort and allow a cooling air flow, reducing helmet temperatures by an average 2-3 degrees.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural	Airports
Construction and Infrastructure	Facilities Management
Forestry & Landscaping	Law Enforcement
Manufacturing	Maritime
Mining, Aggregates and Quarrying	Oil, Gas and Chemical Companies
Rail and Tunnelling	Renewable, Wind and Solar Energy
Scaffolding and Roofing	Sole Trader
Utilities Contractors	

LOGO

- ☑ Front
- ☑ Back
- ☑ Sides

RANGE

evo5 Mk5 evolution DUALSWITCH™

VIDEOS

- www.youtube.com/watch?v=FHdlRqWkD3s
- www.youtube.com/watch?v=pXBgCZzyGII

DOWNLOADS

- Image Pack (ZIP)
- doc-evo5-dualswitch.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.