


## GBC 240HS Home Office A3 Laminator

The GBC 240HS is a sleek and efficient solution for everyday laminating needs. Designed with both style and performance in mind, this high-speed A3 laminator is ideal for home or home office use. Boost productivity and reduce lamination time by 30% using GBC high-speed pouches. With a fast 2-minute warm-up time, it laminates a 75-micron A4 sheet in just 45 seconds, making it perfect for efficiently handling your home projects. The easy-to-use control switch offers three pouch thickness settings from 75-125 microns, providing flexibility for various document types. An anti-jam release lever ensures smooth operation by effortlessly resolving any misfed pouches. Additionally, the smart status LED system simplifies operation with clear visual and audible cues: red during warm-up, blue with a sound when ready, and an automatic shut-off after 15 minutes of inactivity to conserve energy. Protect and preserve your important documents with a perfect finish, every time. Black and red colour.














## Attributes

- Fast warm-up time, ready to use in just 2 minutes.
- Compatible with pouches from 75 to 125 microns. Laminates ID card up to A3 sized documents.
- GBC High-Speed laminators reduce lamination time by 30% when using GBC high-speed pouches.
- Laminates an A4 document (75 mic) in just 45 seconds.
- Laminates 13 x A4 in 10 minutes.
- SMART status LED: glows red during warm-up and turns blue with an acoustic signal when the laminator is ready to use.
- The jam release lever allows easy manual removal of misfed or jammed pouches.
- Includes a starter pack of 5x A4 pouches (75 microns).
- Conserve energy with the 15-minute auto shut-off feature, which activates after detecting inactivity.
- Low noise level <50Dba for less distractions.
- For best results use with GBC document pouches.
- CE certified, TUV/GS.

## Specifications

| | |
|---|---|
| Number | 4410069UK |
| Colour | Black/Red |
| Material | ABS Plastic |
| Dimensions (W x H x D) | 460 x 87 x 151 mm |
| Laminating Speed (mm/min) | 400 |
| Temperature | 123C-135C |
| Power Supply | 220-240V AC 50/60Hz |
| Warm up Time (min) | 2 |
| Heating System | 2 from outside heated rollers |
| Operation Mode | 2 roller, no carrier, temperature controlled |
| Max. Laminating Width (mm) | 330 |
| Max. Laminating Thickness (mm) | 0.5 |
| Max. Pouch Thickness (microns) | 75-125 |
| Power Consumption (W) | 550 |
| Dimensions (with Tray) mm | 460 x 87 x 151 |
| Anti-Jam Technology | Manual release lever |
| Approx. lamination time (A4) | 45 secs (A4 80 micron) |
| Photo friendly | Yes |
| Period of Warranty (Years) | 2 |
| Type | Pouch |
| Weight | 2200 g |
| Pallet quantity | 0 |
| EAN code | 5028252645546 |