# DATASHEET - SMD25




**Fuse-link, low voltage, 25 A, AC 415 V, BS88, 13 x 29 mm, gL/gG, BS**

**Catalog No.** **SMD25**

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 25 |
| Rated voltage | | | AC 415 V |
| Construction size | | | BS88 |
| Size | | | 13 x 29 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | street lighting cut-outs |
| Standard/Approval | | | BS |
| Shape | | | cylindrical |
| Standards/Regulations | | | BS88-1 |

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])

| | | | |
|---|---|---|---|
| Size | | | Other |
| Rated voltage | | V | 415 - 415 |
| Rated voltage | | | Other |
| Voltage type | | | AC |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Rated operating frequency | | Hz | 45 - 62 |
| Nominal current | | A | 25 |
| With striker | | | No |
| Release characteristic | | | Other |
| Breaking capacity | | kA | 80 |



Eaton Industries GmbH
http://www.eaton.eu
© 12/2018 by Eaton Industries GmbH