TYROLA

SIZE 35-48

ESD safety boots

- 4.5 mm studs for maximum grip on all flooring
- Two-fabric upper with orange inserts to highlight the design
- Reflective insert at the heel for better visibility
- ESD Parade shoe: 2 to 15 MΩ



2844 Black

COMPOSITION

Upper	Full-grain leather + Microfiber
Linning	Textile
Toe Cap	Polycarbonate
Stay clean insole	Mesh and ESD PU foam. Removable. Anatomic. Antibacterial. Antifungal.
Puncture proof insert	Non-metallic
Sole	Double density PU/PU
Weight for size 37*	470g
Weight for size 42*	590g

* Weight per shoe

THE PARADE EXCLUSIVE TECHNOLOGIES

VPS SYSTEM — The sole design supports the natural arch of the foot for greater comfort and less tiredness in an upright position.

DRS SYSTEM — An exclusive technology that absorbs the impact for you and provides greater comfort day in day out.

PARADE AIR SYSTEM — An encapsulated air bubble absorbs the micro-impacts of walking.

S3 WET AND RISK FLOOR • NORM: EN ISO 20345: 2011

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole**
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe
- WRU — Water-repellent upper

THE ADDITIONAL FEATURES

Non-magnetic

ESD — Electrostatic dissipation

**

COEFFICIENT OBTAINED FOR SIZE 42	FLAT		HEEL	
	NORM	PARADE	NORM	PARADE
SRA Antislip Ceramic / Nals (soap solution)	0,32	0,37	0,28	0,34
SRB Antislip steel / Glycerine (oil)	0,18	0,27	0,13	0,14

PARADE SAS • Route de Chaudron - BP 36 St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail : commercial@parade-protection.com
Parade reserves the right to modify the characteristics of its products at any time in order to incorporate the latest technological developments.
©Parade, All right reserved. Non contractual document. Version 01 - Update11/2016